
Subject: Re: Pixel Information

Posted by [David Foster](#) on Tue, 02 Dec 1997 08:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

David Fanning wrote:

```
>
> Jonathan Greenspon (jon@eddyco.com) writes:
>
>> I am trying to figure out a method of getting IDL to look at a 640x480
>> image that I have equipment generating, and then take a certain pixel
>> (207,179 - for example) and save the info on that pixel only.
>>
>> Then I can plot out or run an FFT analysis on the values within that
>> point on a given day....
>
> This has got to be a trick question. Oh, all right, I'll
> bite.
>
> How about this:
>
> pixelValues = FltArr(daysTotal)
> FOR eachimage=0,daysTotal-1 DO BEGIN
>   image = OpenImage()
>   pixelValues[eachimage] = image[207,179]
> ENDFOR
> Plot, pixelValues
```

If you will be doing this for many of the pixels repeatedly, then you might want to create a 3D volume out of your 640x480 images:

```
ImgVol = intarr(640,480,Ndays) ; or whatever data-type
ImgVol(*,*,0) = Image1
ImgVol(*,*,1) = Image2 ...
```

and then you can pull out the values of a given pixel over time very quickly with:

```
x = 207
y = 179
PixelValues = ImgVol(x,y,*)
plot, PixelValues
```

Of course you will need lots of memory for this approach, but it's very fast once you create the 3D array.

I have a routine called MAK_VOL that creates a volume out of a list of files (you provide a filespec with ? or *). You'll need to replace the READ_IMG() function with your own function that reads

your particular images, but this would be a good place to start:

`ftp://bial8.ucsd.edu/pub/software/idl/share`

Dave

--

~~~~~  
David S. Foster      Univ. of California, San Diego  
Programmer/Analyst   Brain Image Analysis Laboratory  
foster@bial1.ucsd.edu   Department of Psychiatry  
(619) 622-5892      8950 Via La Jolla Drive, Suite 2240  
                         La Jolla, CA 92037  
~~~~~
