
Subject: Calculating mean (was mean and sdev)
Posted by [Kevin Ivory](#) on Thu, 05 Mar 1998 08:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

Kevin Spencer wrote:

> they get rid of stdev in the first place? And calculating the mean
> is trivial; just use total(x)/n_elements(x).

It is not as trivial as that. If your array contains NaNs, you will always get a NaN as a result. In many cases you will want to have the mean of the finite values.

Another functionality I miss from many IDL routines is the possibility to work on certain array dimensions without having to code loops everywhere. The IDL function total offers this functionality, so my function to code the mean looks like:

```
function average, array, dim, _extra=_extra
;+
; calculates the average value of an array (all arguments as in 'total')
; arguments
; array    array to be averaged, any type except string
; dim      dimension over which to average (see 'total' documentation)
; keywords
; _extra   all keywords passed to 'total'
;-
  if n_elements(dim) eq 0 then dim = 0
  return, total(array, dim, _extra=_extra) / (total(finite(array), dim)>1)
end
```

Best regards

Kevin

--

Kevin Ivory Tel: +49 5556 979 434
Max-Planck-Institut fuer Aeronomie Fax: +49 5556 979 240
Max-Planck-Str. 2 mailto:Kevin.Ivory@linmpi.mpg.de
D-37191 Katlenburg-Lindau, GERMANY http://www.gwdg.de/~kivory2/
