
Subject: Level 1B

Posted by [Kelly Dean](#) on Wed, 11 Mar 1998 08:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

I developed a routine to unpack the 10-bit Level 1B files. I was wondering if anyone can figure out a more efficient method than what I am doing. I use a FOR loop to unpack each record into a 3-dim array (channel, width, height).

Any and all suggesstions welcome.

```
;
;
; Unpack 10-bit values
;
nchan = 5
nx    = 2048 ; always this wide
ny    = 1024 ; can be longer
dim1  = 3414 ; length of 32-bit array of video data
pack  = INTarr(nchan*nx*ny) ; create array for 10-bit data
; Prepare array for index of first 10-bit word
; do not use the first 10-bit value from the last 32-bit value
index1 = LINDGEN(dim1-1) * 3
; Prepare array for index of seocnd 10-bit word
; do not use the second 10-bit value from the last 32-bit value
index2 = LINDGEN(dim1-1) * 3 + 1
; Prepare array for index of third 10-bit word
; the third 10-bit value is used from the 32-bit value
index3 = LINDGEN(dim1) * 3 + 2
; Unpacking 10 bit image data...
FOR ii = 0, NY - 1 DO BEGIN
; remove 32-bit data from data record
  video = REFORM(DataRecords(ii).video, dim1)
; remove the third 10-bit values from the 32-bit values
  pack(index3) = FIX(video AND '3FF'X)
; remove the second 10-bit values from the 32-bit values
  pack(index2) = FIX(ISHFT(video(0:3412),-10) AND '3FF'X)
; remove the first 10-bit values from the 32-bit values
  pack(index1) = FIX(ISHFT(video(0:3412),-20) AND '3FF'X)
; update pack array index for next video record.
  index1 = index1 + ( 3 * dim1 ) - 2
  index2 = index2 + ( 3 * dim1 ) - 2
  index3 = index3 + ( 3 * dim1 ) - 2
ENDFOR
;reformat array to 3-dim ( channels, width, height )
image = REFORM(pack,nchan,nx,ny)
```

Kelly Dean

