

---

Subject: Re: Deleting Variables

Posted by [thompson](#) on Fri, 24 Apr 1998 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

lundblad@ugastro.berkeley.edu (Nathan Lundblad) writes:

> How does one delete variable in IDL?

> I know `_delvar_`, but that only works on the  
> main level of the program, and only one on  
> variable. I want to purge everything.

> Also, how would one delete a common block?

I don't think one can delete an entire common block. However, here is simple routine that can delete any variable, even those in subroutines or common blocks. Actually, it sets them to undefined, which is almost the same thing.

Bill Thompson

```
=====
=====
pro delvarx, p0,p1,p2,p3,p4,p5,p6,p7,p8,p9
;
;+
;
; Project: SSW
;
; Name: delvarx
;
; Purpose: delete variables for memory management (can call from routines)
;
; Input Parameters:
;   p0,p1...p9 - variables to delete
;
; Calling Sequence:
;   delvarx, a [,b,c,d,e,f,g,h,i,j] ;deletes named variables
;   ;like idl delvar, but may be used
;   ;from any calling level
;
; History:
;   S.L.Freeland 25-feb-1993      ; Written
;   slf, 8-mar-1993  ; bug fix
;   slf, 25-mar-1993  ; made it work for non-scalars!
;   slf, 15-jan-1997      ; Documentataion->SSW
;
;
```

```
; Method: uses execute and temporary function
;-
for i=0, n_params()-1 do begin      ;for each parameter
    param=strcompress("p" + string(i),/remove)
; only delete if defined on input (avoids error message)
    exestat = execute("defined=n_elements(" + param + ")")
    if defined gt 0 then begin
        exestat = execute(param + "=0")
        exestat = execute("dvar=temporary(" + param + ")")
    endif
endfor
return
end
```

---