

---

Subject: Re: Q: Multiple File select  
Posted by [pit](#) on Mon, 04 May 1998 07:00:00 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

In article <354CB4C9.22A9@erols.com>,  
biomedical <[biomedic@erols.com](mailto:biomedic@erols.com)> writes:  
> Could you just post it as text file.  
> I don't have tools to gunzip it.

Shure, but why do you quote the whole file for that??

Peter

---

```
;+
; NAME:
;   PICKFILES
;
; PURPOSE:
;   This function allows the user to interactively pick one or more
;   file(s). A file selection tool with a graphical user interface
;   is created. Files can be selected and deselected from the
;   current directory or other directories.
;
; CATEGORY:
;   Widgets.
;
; CALLING SEQUENCE:
;   Result = PICKFILES()
;
; KEYWORD PARAMETERS:
;
;   FILE: (input) A string or string array for setting the initial
;         value of the selection. Useful if there is a default file
;
;   GROUP: (input) The widget ID of the widget that calls PICKFILE.
;          When this ID is specified, a death of the caller results
;          in the death of the PICKFILE widget application.
;
;   READ: (Flag) Set this keyword to make the title of the PICKFILE
;         window "Select File(s) to Read".
;
;   WRITE: (Flag) Set this keyword to make the title of the PICKFILE
;         window "Select File(s) to Write".
;
;   PATH: (input) The initial path to select files from. If this
;         keyword is not set, the current directory is used.
;
;   FILTER: (input) A string value for filtering the files in the
```

; file list. This keyword is used to reduce the number of  
; files to choose from. The user can modify the filter  
; unless the FIX\_FILTER keyword is set. Example filter  
; values might be "\*.pro" or "\*.dat".

; FIX\_FILTER: (Flag) When this keyword is set, only files that  
; satisfy the filter can be selected. The user has no  
; ability to modify the filter and the filter is not shown.

; TITLE: (input) A scalar string to be used for the window title.  
; If it is not specified, the default title is "Select File"

; MUST\_EXIST: (Flag) When set, only files that actually exist can  
; be selected.

; POSITION: (input) 2-el vector with position of upper left  
; corner of the widget base, counted from top left  
; screen corner. May be ignored depending on your window  
; manager.

; OUTPUTS:  
; PICKFILE returns a string or string array that contains the name  
; of the file(s) selected. If no file is selected, PICKFILE  
; returns a null string.

; COMMON BLOCKS:  
; PICKER: COMMON block that maintains state for the widget.

; SIDE EFFECTS:  
; This function initiates the XMANAGER if it is not already running.

; RESTRICTIONS:  
; This routine is known to work on Suns (OPEN LOOK), MIPS, RS/6000,  
; DEC Ultrix, HP/700, VAX/VMS, SGI and Linux machines.  
;  
; Only one instance of the PICKFILE widget can be running at one time.  
;  
; PICKFILE does not recognize symbolic links to other files in UNIX.

; PROCEDURE:  
; Create and register the widget and then exit, returning the  
; filename(s) that were picked.

; EXAMPLE:  
; Create a PICKFILE widget that lets users select only files with  
; the extensions 'pro' and 'dat'. Use the 'Select File to Read' title  
; and store the name of the selected file in the variable F. Enter:

```
F = PICKFILE(/READ, FILTER = '*.pro *.dat')

;MODIFICATION HISTORY:
; Written by: Steve Richards, April, 1991
; July, 1991 Added a FILTER keyword to allow users
; to select files with a given extension or
; extensions.
; August, 1991 Fixed bugs caused by differences between
; spawned ls commands on different machines.
; September, 1991 Made Myfindfile so only one pass was
; necessary to find files and directories.
; 3/92 - ACY Corrected initialization of dirsav, change spawn
; command to "ls -IL" and added case for links
; add NOCONFIRM keyword for auto exiting on selection
; 8/92 - SMR Rewrote pickfile as a compound widget.
; 10/92 - SMR Fixed a bug where extremely large file names didn't
; show up properly in the file list or as return
; values.
; 12/92 - JWG Add better machine dependency code
; 1/93 - JWG Added FILE, GET_PATH keywords.
; 1/93 - TAC Added Windows Common dialog pickfile code
; 2/93 - SMR Fixed the documentation example for multiple extensions
; 1/94 - KDB If directory had no execute permission on Unix
; platforms, CD fails and causes error. Added check
; for this. Increased spawn speed by using /sh for unix.
; Added -a switch to ls so that all files can be found
; on unix machines.
; 2/94 - KDB Values passed to CD cannot end in a '\' on DOS
; platforms. Program would crash if the PATH keyword
; was supplied a value that ended with a "\". Added
; a check for this.
; 3/94 - BMH Deleted the reference here to OS_PICKFILE for the
; Unix platforms and created an IDL routine to
; to call the Mac and Windows specific OS_PICKFILE
; routines. This solved the saving and restoring on
; different platforms problem.
; 4/94 - KDB The vms call to lib$findfile in valid_dir was
; commented out. This caused errors when path was
; changed by user. Uncommented. In Valid_Dir, with
; vms the type of directory specification was not
; checked (directory can be a path or a filename):
; Fixed this. In dirlist section of event handler,
; a "[-]" would get trimmed to "" and cause error:
; Fixed.
; 8/94 - ACY Change the spawn command in getdirs to send error
; output to /dev/null.
; 12/94 - DJE Fix the FIX_FILTER option for the MacOS.
; 9/95 - PS change to multfile-selection. Remove keywords
```

```
; NOCONFIRM and GET_PATH, which don't have a useful  
; meaning any more. Added POSITION Keyword.  
; 4/96 - PS Add Select all button  
;  
;-  
;
```

FUNCTION valid\_dir, dir

WIDGET\_CONTROL, /HOUR

```
; Can't CD to a directory unless the user has execute permission.  
; Use the unix command test to check this. Have to use sh5 on ultrix  
; Test sets the shell status variable and echo prints it out. This is  
; then captured by spawn and placed in result
```

```
IF (!version.os NE 'ultrix') THEN BEGIN  
    spawn, ['test -d "+dir +" -a -x "+dir+" ; echo $?'], result, /sh  
ENDIF ELSE BEGIN  
    spawn, ['/bin/sh5 -c "test -d "+dir+" -a -x "+dir+$  
        " ";echo $?'], result, /sh  
ENDELSE
```

return, (not fix(result(0)) ) ;convert result to int and NOT it.

END

```
-----  
; procedure GETDIR  
-----  
; This routine finds the files or directories at the current directory level.  
; It must be called with either files or directories as a keyword.  
-----
```

function getdirs

WIDGET\_CONTROL, /HOUR

```
retval = ['..']  
;added -a switch to get .* dirs  
;change to /noshell, send errors to /dev/null  
SPAWN, ["/bin/sh", "-c", "ls -laL 2>/dev/null"], /NOSHELL, results  
numfound = N_ELEMENTS(results)  
IF(KEYWORD_SET(results)) THEN BEGIN ;extension of ".dir"  
    firsts = STRUPCASE(STRMID(results, 0, 1))  
    dirs = (where(firsts EQ "D", found))  
    IF (found GT 0) THEN BEGIN  
        results = results(dirs)
```

```

spaceinds = WHERE(BYTE(results(0)) EQ 32)
spaceindex = spaceinds(N_ELEMENTS(spaceinds)-1)
retval = [retval, STRMID(results, spaceindex + 1, 100)]
;;; get rid of "." and ".." that ls -laL picks up
retval = retval(WHERE( (retval ne '.')and(retval ne '..')) )
ENDIF
ENDIF
RETURN, retval
END ; function getdirs

```

-----;

FUNCTION getfiles, filter

WIDGET\_CONTROL, /HOUR

```

SPAWN, [/bin/sh, "-c", "ls -laL " + filter + $
" 2> /dev/null"], results, /NOSHELL ;added -a to get all files

```

```

IF(KEYWORD_SET(results)) THEN BEGIN
    firsts = STRUPCASE(STRMID(results, 0, 1))
    fileinds = (WHERE(((firsts EQ "F") OR (firsts EQ "-") OR $ 
        (firsts EQ "I")), found))
    IF (found GT 0) THEN BEGIN
        results = results(fileinds)
        FOR i=0, N_ELEMENTS(results) - 1 DO BEGIN
            spaceinds = WHERE(BYTE(results(i)) EQ 32)
            spaceindex = spaceinds(N_ELEMENTS(spaceinds) - 1)
            results(i) = STRMID(results(i), spaceindex + 1, 100)
        ENDFOR
        RETURN, results
    ENDIF
ENDIF
RETURN, ""
END

```

-----;

; procedure Pickfile\_ev

-----;

; This procedure processes the events being sent by the XManager.

-----;

PRO Pickfile\_ev, event

```

COMMON newpicker, pathtxt, filetxt, dirlist, filelist, sel_list, $
ok, selall, cancel, help, here, thefile, separator, $
swapbutt, swap_dat

```

WIDGET\_CONTROL, filetxt, GET\_VALUE = filt

```
filt = filt(0)
```

```
CASE event.id OF
```

```
cancel: BEGIN
    thefile = ""
    WIDGET_CONTROL, event.top, /DESTROY
END
```

```
filetxt: BEGIN
    files = getfiles(filt)
    WIDGET_CONTROL, filelist, SET_VALUE = files
    WIDGET_CONTROL, filelist, SET_UVALUE = files
END
```

```
selall: BEGIN
    WIDGET_CONTROL, filelist, GET_UVALUE = files
    IF (KEYWORD_SET(files)) THEN BEGIN
        thefile = here + files
        WIDGET_CONTROL, sel_list, GET_UVALUE=selectlist
        IF selectlist(0) EQ " THEN BEGIN
            selectlist = thefile
        ENDIF

        FOR i=0, n_elements(thefile)-1 DO BEGIN
            IF max((selpos=where(strpos(selectlist, thefile(i)) $ GE 0))) LT 0 THEN $
                selectlist = [selectlist, thefile(i)]
        ENDFOR
        WIDGET_CONTROL, sel_list, SET_VALUE=selectlist
        WIDGET_CONTROL, sel_list, SET_UVALUE=selectlist
    ENDIF
END
```

```
dirlist: BEGIN
    WIDGET_CONTROL, dirlist, GET_UVALUE = directories
    IF (event.index GT N_ELEMENTS(directories) - 1) THEN RETURN
```

```
; Check an see if the directory is valid
if(not valid_dir(directories(event.index)) ) then return

IF (!version.os EQ "vms") THEN BEGIN
; Fixed logic error. If the users selects [-], the strpos/mid
; combo would return a null string. Added a check for [-],index=0

    if(event.index eq 0)then $
        found = 3   $ ; len of [-]
```

```

else    $
found = STRPOS(directories(event.index), ".", 0)

CD, STRMID(directories(event.index), 0, found)
CD, CURRENT = here ;get pwd

ENDIF ELSE IF !version.os EQ 'Win32' THEN BEGIN
  message,"Unsupported on this platform"
ENDIF ELSE BEGIN
  CD, directories(event.index)
  CD, CURRENT = here
  here = here + separator
ENDELSE
WIDGET_CONTROL, pathtxt, SET_VALUE = here
directories = getdirs()
files = getfiles(filt)
WIDGET_CONTROL, filelist, SET_VALUE = files
WIDGET_CONTROL, filelist, SET_UVALUE = files
WIDGET_CONTROL, dirlist, SET_VALUE = directories
WIDGET_CONTROL, dirlist, SET_UVALUE = directories
END

```

```

pathtxt: BEGIN
  WIDGET_CONTROL, pathtxt, GET_VALUE = newpath
  newpath = newpath(0)
  len = STRLEN(newpath) - 1
  IF STRPOS(newpath, '/', len) NE -1 THEN $
    newpath = STRMID(newpath, 0, len)
  IF (valid_dir(newpath(0))) THEN BEGIN
    here = newpath(0) + separator
    CD, here
    directories = getdirs()
    files = getfiles(filt)
    WIDGET_CONTROL, filelist, SET_VALUE = files
    WIDGET_CONTROL, filelist, SET_UVALUE = files
    WIDGET_CONTROL, dirlist, SET_VALUE = directories
    WIDGET_CONTROL, dirlist, SET_UVALUE = directories
  ENDIF ELSE $
    WIDGET_CONTROL, pathtxt, SET_VALUE = here
END

```

```

filelist: BEGIN
  WIDGET_CONTROL, filelist, GET_UVALUE = files
  IF (KEYWORD_SET(files)) THEN BEGIN
    thefile = here + files(event.index)
    WIDGET_CONTROL, sel_list, GET_UVALUE=selectlist
    IF selectlist(0) EQ " THEN BEGIN
      selectlist = thefile

```

```

WIDGET_CONTROL, sel_list, SET_VALUE=selectlist
WIDGET_CONTROL, sel_list, SET_UVALUE=selectlist
ENDIF
IF max((selpos=where(strpos(selectlist, thefile) GE 0))) LT 0 THEN BEGIN
    selectlist = [selectlist, thefile]
    WIDGET_CONTROL, sel_list, SET_VALUE=selectlist
    WIDGET_CONTROL, sel_list, SET_UVALUE=selectlist
ENDIF ELSE BEGIN
    ;; check for substrings
    selpos = selpos(where(selpos GE 0))
    FOR i=0, n_elements(selpos)-1 DO $
        IF thefile EQ selectlist(selpos(i)) THEN GOTO, have_it
        selectlist = [selectlist, thefile]
        WIDGET_CONTROL, sel_list, SET_VALUE=selectlist
        WIDGET_CONTROL, sel_list, SET_UVALUE=selectlist
    Have_it:
ENDIF
ENDELSE
WIDGET_CONTROL, ok, GET_UVALUE=auto_exit
IF (auto_exit) THEN GOTO, checkfile
ENDIF
END

```

ok: GOTO, checkfile

```

Sel_list: BEGIN
    WIDGET_CONTROL, sel_list, GET_UVALUE=selectlist
    IF (KEYWORD_SET(selectlist)) THEN BEGIN
        thefile = selectlist(event.index)
        nf = n_elements(selectlist)
        CASE event.index OF
            0: BEGIN
                IF nf EQ 1 THEN $
                    selectlist = " "
                ELSE $
                    selectlist = selectlist(1:*)
            END
            nf-1: BEGIN
                IF nf EQ 1 THEN $
                    selectlist = " "
                ELSE $
                    selectlist = selectlist(0:nf-2)
            END
            Else: selectlist = [ selectlist(0:event.index-1), $
                                selectlist(event.index+1:*)]
        ENDCASE
        WIDGET_CONTROL, sel_list, SET_VALUE=selectlist
        WIDGET_CONTROL, sel_list, SET_UVALUE=selectlist
    ENDIF

```

END

```
Swapbutt: BEGIN
    widget_control, swapbutt, get_val=butt_stat
    swap_dat = where(['No', 'Yes'] EQ butt_stat)
    swap_dat = swap_dat XOR 1
    widget_control, swapbutt, set_val=(['No', 'Yes'])(swap_dat(0))
END
```

```
Help: XDISPLAYFILE, "", $
GROUP=event.top, $
TITLE="File Selection Help", $
WIDTH=50, $
HEIGHT=13, $
TEXT=["
    This file selection widget lets you pick one",
    "or more files. The files are shown on the right.", "
    "You can select a file by clicking on it with the",
    "mouse. The selections are shown in the lower",
    "frame. You can also deselect them there via",
    "mouseupclick. Pressing the 'OK' button will accept",
    "the choice and the Cancel button will not. To",
    "move into a subdirectory, click on its name in",
    "the directory list on the left. The path can",
    "also be modified to view files from a different",
    "directory. The list of files can be modified by",
    "typing in a filter."]
```

```
ENDCASE
RETURN
```

```
checkfile:
WIDGET_CONTROL, sel_list, GET_UVALUE = temp
WIDGET_CONTROL, cancel, GET_UVALUE = existflag
widget_control, swapbutt, get_val=butt_stat
swap_dat = where(['No', 'Yes'] EQ butt_stat)
IF existflag THEN BEGIN
    ON_IOERROR, print_error
    FOR i=0, n_elements(temp) DO BEGIN
        OPENR, unit, temp(0), /GET_LUN
        FREE_LUN, unit
    ENDFOR
ENDIF
thefile = temp
WIDGET_CONTROL, event.top, /DESTROY
RETURN
```

```
print_error:
    WIDGET_CONTROL, selecttxt, SET_VALUE = "!!! Invalid File Name !!!"
```

```

thefile = ""

END ;===== end of Pickfile event handling routine task =====

;

;----- procedure Pickfile
;----- This is the actual routine that creates the widget and registers it with the
; Xmanager. It also determines the operating system and sets the specific
; file designators for that operating system.
;----- FUNCTION Pickfiles, GROUP=GROUP, PATH=PATH, READ=READ, WRITE=WRITE, $
; FILTER=FILTER, TITLE=TITLE, MUST_EXIST=MUST_EXIST, $
; FIX_FILTER=FIX_FILTER, FILE=FILE, SWAP_DATA=SWAP_DATA, $
; POSITION=pos

COMMON newpicker, pathtxt, filetxt, dirlist, filelist, sel_list, $
ok, selall, cancel, help, here, thefile, separator, $
swapbutt, swap_dat

IF(XRegistered("Pickfile")) THEN RETURN, 0

thefile = ""
existflag = 0

separator      = '/'

CD, CURRENT = dirsav

IF (N_ELEMENTS(PATH) EQ 0) THEN BEGIN
  PATH = dirsav + separator
  here = PATH
ENDIF ELSE BEGIN
  IF(STRPOS(PATH, separator, STRLEN(PATH)- 1) EQ -1)$
    AND (PATH NE separator)THEN $
    PATH = PATH + separator
  CD, PATH          ;if the user selected
  here = PATH        ;a path then use it
ENDIFELSE

IF (KEYWORD_SET(NOCONFIRM)) THEN auto_exit = 1 ELSE auto_exit = 0
IF (KEYWORD_SET(MUST_EXIST)) THEN existflag = 1 ELSE existflag = 0
IF (KEYWORD_SET(FIX_FILTER)) THEN mapfilter = 0 ELSE mapfilter = 1
IF keyword_set(swap_data) THEN map_swap = 1 ELSE BEGIN
  map_swap = 0
  swap_data = 0

```

```

ENDELSE
swap_dat = swap_data

IF (N_ELEMENTS(FILE) EQ 0) THEN FILE = ""

IF (NOT (KEYWORD_SET(TITLE))) THEN $           ;build up the title
  TITLE = "Please Select the File(s)"          ;based on the keywords

IF (KEYWORD_SET(READ)) THEN TITLE = TITLE + " for Reading" $
ELSE IF (KEYWORD_SET(WRITE)) THEN TITLE = TITLE + " for Writing"

IF (KEYWORD_SET(FILTER)) THEN filt = FILTER ELSE filt = ""

directories = getdirs()
files = getfiles(filt)

version = WIDGET_INFO(/VERSION)
IF (version.style EQ 'Motif') THEN osfrm = 0 ELSE osfrm = 1

Pickfilebase = WIDGET_BASE(TITLE=TITLE, /COLUMN)
widebase = widget_label(Pickfilebase, value=title)
widebase = WIDGET_BASE(Pickfilebase, /ROW)
label = WIDGET_LABEL(widebase, VALUE="Path:")
pathtxt = WIDGET_TEXT(widebase, VAL=here, /EDIT, FR=osfrm, XS=50)
filtbase = WIDGET_BASE(Pickfilebase, /ROW, MAP=mapfilter)
filtlbl = WIDGET_LABEL(filtbase, VALUE="Filter:")
filttxt = WIDGET_TEXT(filtbase, VAL=filt, /EDIT, XS=10, FR=osfrm)
selections = WIDGET_BASE(Pickfilebase, /ROW, SPACE=30)
dirs = WIDGET_BASE(selections, /COLUMN, /FRAME)
lbl = WIDGET_LABEL(dirs, VALUE="Subdirectories      ")
dirlist = WIDGET_LIST(dirs, VALUE=directories, YSIZE=8, $
                      UVALUE=directories)
fls = WIDGET_BASE(selections, /COLUMN, /FRAME)
lbl = WIDGET_LABEL(fls, VALUE="Files      ")
filelist = WIDGET_LIST(fls, VALUE=files, YSIZE=8, $
                      UVALUE=files)
widebase = WIDGET_BASE(Pickfilebase, /COLUMN, /frame)
label = WIDGET_LABEL(widebase, VALUE="Selection(s)      ")
sel_list = WIDGET_LIST(widebase, value=file, uval=file, ys=10, xs=40)

rowbase = widget_base(Pickfilebase, /row, map=map_swap)
label = widget_label(rowbase, value='Byteswap Image data ?')
swapbutt = widget_button(rowbase, val=(['No', 'Yes'])(swap_dat))

rowbase = WIDGET_BASE(Pickfilebase, SPACE=20, /ROW)
ok = WIDGET_BUTTON(rowbase, VALUE=" Ok ", $
                   UVALUE=auto_exit)

```

```

selall = WIDGET_BUTTON(rowbase, VALUE=" Select all ")
cancel = WIDGET_BUTTON(rowbase, VALUE=" Cancel ", $  

                      UVALUE=existflag)
help = WIDGET_BUTTON(rowbase, VALUE=" Help ")

IF keyword_set(pos) THEN $  

  widget_control, Pickfilebase, xoff=pos(0), yoff=pos(1)

WIDGET_CONTROL, Pickfilebase, /REALIZE

XManager, "Pickfile", Pickfilebase, EVENT_HANDLER="Pickfile_ev", $  

  GROUP_LEADER=GROUP, /MODAL

CD, dirsav
filt = ""
swap_data = swap_dat(0)

RETURN, thefile

END ;===== end of Pickfile routine =====

```

--  
~~~~~  
~~~~~  
Peter "Pit" Suetterlin http://www.uni-sw.gwdg.de/~pit  
Universitaets-Sternwarte Goettingen  
Tel.: +49 551 39-5048 pit@uni-sw.gwdg.de  
-- \* -- \* ...-- \* -- \* ...-- \* -- \* ...-- \* -- \* ...-- \* --  
Come and see the stars! http://www.kis.uni-freiburg.de/~ps/SFB  
Sternfreunde Breisgau e.V. Tel.: +49 7641 3492

---



---