

---

Subject: Re: Longword plotting problems...

Posted by [menakkis](#) on Mon, 22 Jun 1998 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

"Geraint H. Jones" <g.h.jones@ic.ac.uk> wrote:

```
> I'm handling data files (well, trying to!) in which the time is recorded
> as the number of seconds since the beginning of 1950 (I know it's not
> the easiest format to deal with, but it's what I have to work with). In
> order to get precision to the level of seconds, I have to use longword
> arrays.
>
> This is all fine, but the problem is plotting using the longword arrays.
> Whatever plot ranges I choose, the time values in the plots are
> quantized, i.e. they do not increase smoothly, even though the values
> in the array itself increase smoothly. I've attached a short piece of
> example code below to demonstrate this...
>
> ; Example code
>
> time=lindgen(10)+13254100
>
> data=findgen(10)
>
> plot,time,data
```

I think that there's no way to do this the way you'd like. What's happening is that your times are using well over 24 bits in the longwords, and the FLOAT format can only represent integers accurately if they use about 24 bits - any more is simply lost (from the "small end"). Unfortunately, the PLOT routine (& friends) converts its arguments to FLOAT. A "double misfortune" (sorry :- ) - even if you pass DOUBLE arguments to PLOT, it will convert them to FLOAT!

Perhaps you could plot offset-removed seconds across X; i.e., first subtract the smallest time value.

(BTW, I had to use `time=lindgen(10)+'0ffffff'x` to get your example to really kick.)

Peter Mason

-----= Posted via Deja News, The Leader in Internet Discussion =-----  
<http://www.dejanews.com/> Now offering spam-free web-based newsreading

---