
Subject: Re: buttons on exclusive base

Posted by [David Foster](#) on Fri, 12 Jun 1998 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

csaute3@alumni.umbc.edu wrote:

>
> I have an exclusive base created by WIDGET_BASE(/EXCLUSIVE).
> (It can only have button children and only one button can be
> set at a time.) I use
>
> WIDGET_CONTROL, button, SET_BUTTON=1
>
> to select one button on in my main routine for my default and
> the rest of the buttons are off.
>
> Question: In my event loop, how do determine which button is
> on? Is there a keyword to WIDGET_INFO?
>
> Or should I create an array with the number of elements equal
> to the number of buttons and the values equal to 1/0 if a
> button is on/off? I don't want to maintain this array every
> time a toggle button is pushed, but if it's the only way ...
>
> Cathy

I believe that if you use CW_BGROUPO() to create your exclusive
button group, you can use WIDGET_CONTROL, group_base, get_value=
to get the index of the currently selected button.

Dave

--

~~~~~  
David S. Foster      Univ. of California, San Diego  
Programmer/Analyst   Brain Image Analysis Laboratory  
foster@bials1.ucsd.edu   Department of Psychiatry  
(619) 622-5892      8950 Via La Jolla Drive, Suite 2240  
La Jolla, CA 92037  
~~~~~