Subject: Re: array subscripts
Posted by Kevin Ivory on Fri, 18 Sep 1998 07:00:00 GMT
View Forum Message <> Reply to Message

> Martin Schultz (mgs@io.harvard.edu) writes:
>> PPS: And while we are at it... One of the most useful tips I got from
>> David's book (so far) was the A[n:*] syntax to extract ranges from n to
>> end. I am really grateful for this!

David Fanning wrote:
> I've been using this for so long I can't really remember
> where I learned it, but I suspect it was from Ray Sterner's
> unpublished (so far) IDL manuscript. He has dozens of
> useful subscripting tips like this. :-)

Perhaps you read the IDL manual? The book 'Building IDL Applications' has a chapter about 'Array Subscripts' with a section about 'Subscript Ranges'. ;-)

By the way, the book is online:
ftp://ftp.rsinc.com/pub/idl_5.1.1/info/docs/building.pdf
See page 62.

Cheers,
Kevin
--
Kevin Ivory Tel: +49 5556 979 434
Max-Planck-Institut fuer Aeronomie Fax: +49 5556 979 240
Max-Planck-Str. 2 mailto:Kevin.Ivory@linmpi.mpg.de
D-37191 Katlenburg-Lindau, GERMANY http://www.gwdg.de/~kivory2/