
Subject: Re: Copying IDL objects

Posted by [davidf](#) on Fri, 02 Oct 1998 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Folks,

I wrote just a couple of minutes ago:

```
> This seems like a lot of work. I think I would write this
> function something like this:
>
>   PRO My_Obj::Copy, out
>   tags = N_Tags(self)
>   For j=0,tags-1 DO out.(j) = self.(j)
>   END
```

Mark Rivers kindly points out to me that this doesn't work, for the simple reason that self is not a structure (even though it can be accessed as if it were a structure in a method). Thus, N_Tags returns a 0.

To make it work, I have to do this (with a bit of error checking too :-):

```
   PRO My_Obj::Copy, out
   selfClass = Obj_Class(self)
   outClass = Obj_Class(out)
   IF selfClass NE outClass THEN BEGIN
ok = Dialog_Message('Object classes not identical.')
   RETURN
   END
   ok = Execute('struct = {' + selfClass + '}')
   tags = N_Tags(struct)
   For j=0,tags-1 DO out.(j) = self.(j)
   END
```

Cheers,

David

David Fanning, Ph.D.

Fanning Software Consulting

E-Mail: davidf@dfanning.com

Phone: 970-221-0438, Toll-Free Book Orders: 1-888-461-0155

Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
