
Subject: Re: Group leader

Posted by [David Foster](#) on Wed, 14 Oct 1998 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Imanol Echave wrote:

>
> Hi people:
>
> I have a little question: What is the difference between the GROUP_LEADER
> keyword on XMANAGER and the same keyword used on a top-level base? Do they work
> on the same way?

Imanol -

As far as I know, they serve the same purpose. the GROUP_LEADER keyword to WIDGET_BASE() is more recent, and it's my impression that it is "preferable" to use the keyword here rather than in the XMANAGER call.

I have a modal popup information widget that just comes up and says "Please wait...busy doing < >...", and then after some processing the widget is killed by the calling module. In this case, since this widget doesn't generate any events, you don't register it with XMANAGER. But I *do* want it to have a GROUP_LEADER, so I declare it in the call to WIDGET_BASE() for the popup widget.

Dave

--

~~~~~  
David S. Foster      Univ. of California, San Diego  
Programmer/Analyst   Brain Image Analysis Laboratory  
foster@bial1.ucsd.edu   Department of Psychiatry  
(619) 622-5892      8950 Via La Jolla Drive, Suite 2240  
                         La Jolla, CA 92037  
~~~~~