
Subject: Re: Group leader

Posted by [davidf](#) on Sat, 24 Oct 1998 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Imanol Echave (ccaeccai@sc.ehu.es) writes:

- > I have a little question: What is the difference between the GROUP_LEADER
- > keyword on XMANAGER and the same keyword used on a top-level base? Do they work
- > on the same way?

In this case it doesn't matter at all whether you assign the group leader to the top-level base with the GROUP_LEADER keyword when you create the TLB or when you call XMANAGER, but this is not always the case with the TLB. For example, you should never use the EVENT_PRO keyword to assign the event procedure to a TLB; always use the EVENT_HANDLER keyword on XMANAGER. Similarly, you should never use the KILL_NOTIFY keyword to assign a clean-up routine to the TLB; always use the CLEANUP keyword on XMANAGER.

Failure to heed these warnings causes some VERY strange behaviour in widget programs. And the warnings in the documentation are worded in such a way that many people miss them. :-)

Cheers,

David

David Fanning, Ph.D.

Fanning Software Consulting

E-Mail: davidf@dfanning.com

Phone: 970-221-0438, Toll-Free Book Orders: 1-888-461-0155

Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
