

---

Subject: Re: Dumb Dumb Question

Posted by [R.Bauer](#) on Tue, 24 Nov 1998 08:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Colin Rosenthal wrote:

```
> This may be really stupid, but is there a way around the following
> feature:
>
> pro x_test,x=x,x2=x2
>   if n_elements(x) ne 0 then print, 'x=',x
>   if n_elements(x2) ne 0 then print, 'x2=',x2
> end
>
> when I run it with
>> x_test,x=1
> I get
> % Ambiguous keyword abbreviation: X.
> % Execution halted at: $MAIN$
>
> Does this mean no IDL procedure will ever work if one keyword is a left
> substring of another keyword? Can I force IDL to interpret the "x" as "x"
> and not an ambiguous abbreviation for "x2"?
>
```

Both yes:

But you can use a little trick like that:

```
FUNCTION is_tag,struct,tag_name
  tagname=STRUPCASE(tag_name)
  tags=TAG_NAMES(struct)
  a=WHERE(tags EQ tagname,count)
  RETURN, count
END
```

```
pro x_test,_extra=pkey
  if is_tag(pkey,'x')then print, 'x=',pkey.x
  if is_tag(pkey,'x2') ne 0 then print, 'x2=',pkey.x2
end
```

R Bauer

---