
Subject: Re: outputting formated text version of code
Posted by [R.Bauer](#) on Mon, 07 Dec 1998 08:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

```
<!doctype html public "-//w3c//dtd html 4.0 transitional//en">
<html>
&nbsp;
<p>Brad Gom wrote:
<blockquote TYPE=CITE>&nbsp;
<p>R.Bauer wrote:
<blockquote TYPE=CITE>&nbsp;
<br>Do you think about something like this?
<p><font color="#009900"> ;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp; ; Written
by:&nbsp;&nbsp;&nbsp; R.Bauer (ICG-1), 1998-Dec-07</font>
<br><font color="#009900">:-</font>
<br><font color="#CC0000">PRO</font><font color="#000000"> x_breaker_event,ev</font>
<br><font color="#000000">&nbsp;&nbsp; </font><font
color="#000099">WIDGET_CONTROL</font><font color="#000000">,
ev.id, get_uval=cmd</font>
<br>&nbsp;</blockquote>
Yep, exactly. I assume you have control over the html codes that are generated?
<p>Brad Gom</blockquote>
Yes, I have.
<br>It uppercases the RSI Routines too and did the formatting of&nbsp;
the whole syntax
<br>and it is written totally in IDL .
<p>Now I think you will ask if you can use it.
<p>Yes, but you have to wait a few days, because it is part of a library
which we will published I hope before Christmas.
<br>&nbsp;
<p>R.Bauer
<br>&nbsp;
<br>&nbsp;</html>
```
