
Subject: Re: Passing a structured variable as an argument of procedure

Posted by [Martin Schultz](#) on Mon, 22 Mar 1999 08:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

VU KHAC Tri wrote:

>
> Hi folks,
>
> I'm very new in IDL programming.
> My question is can I pass a structured variable as an argument of a
> procedure ?
> How to define this ?

(A) if you create a structure outside of your procedure, you can pass it like any other variable either as parameter or keyword:

```
a = { test:'my name', value=100 }
```

```
my_proc,a
```

```
or my_proc,structure=a
```

(you may find my little chkstru function helpful to test whether what you passed really is a structure and [optionally] if it contains the fields ("tags") that you need. You can get it from my webpage (see below)).

(B) same thing holds if you create your structure within your procedure.

Example:

```
pro my_proc,newstru
```

```
newstru = { dummy:1.0, truevalue:1 }  
end
```

(and in "main"):

```
my_proc,test  
print,test
```

Hope this helps,
Martin.

--

Dr. Martin Schultz
Department for Engineering&Applied Sciences, Harvard University
109 Pierce Hall, 29 Oxford St., Cambridge, MA-02138, USA

phone: (617)-496-8318
fax : (617)-495-4551

e-mail: mgs@io.harvard.edu
Internet-homepage: <http://www-as.harvard.edu/people/staff/mgs/>
