
Subject: Re: coherence test implementation
Posted by [Dick Jackson](#) on Thu, 13 May 1999 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Mark,

Mark Rehbein wrote:

>
> Hi,
>
> I'm doing some cloud detection on some rather large images using what
> some people call a coherence test. To do a coherence test on a pixel
> you take a 3x3 matrix around that pixel and assign that pixel the
> standard deviation of the 3x3 matrix.

You piqued my curiosity, since you're right, there had to be a more efficient way! My attached coherence.pro should do the trick, and I clock it at about 60 times faster with a 300x300 test.

From your code, just call:

```
sddevimage = Coherence(ch4)
```

I return an image of the same size and leave the outer ring of pixels as 0.0, is that reasonable?

I used the formula for the SD of a set of 9 values:

$$SD = \sqrt{((\text{Sum}(X^2) - (\text{Sum}(X)^2 / 9)) / 8)}$$

Generalizing coherence.pro to allow variable 'width' (not fixed at 3) is left as an exercise to the reader. :-) I guess it wouldn't be hard, changing all 'magic numbers' (3, 2, 9 and 8) to width, width-1, width^2 and width^2-1.

Cheers,

--

-Dick

Dick Jackson Fanning Software Consulting, Canadian Office
djackson@dfanning.com Calgary, Alberta Voice/Fax: (403) 242-7398
Coyote's Guide to IDL Programming: <http://www.dfanning.com/>

File Attachments

1) [coherence.pro](#), downloaded 101 times
