
Subject: Re: Passing zero as a Parameter/ NOT KEYWORD_SET

Posted by [R.Bauer](#) on Wed, 30 Jun 1999 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Martin Schultz wrote:

> J.D. Smith wrote:

>>

>>

>> That's a bit dangerous. [...]

> Indeed ;-)

>>

>> The best way to proceed is pretend keyword_set() was really

>> named is_defined_and_non_zero(). Forget that it's called

>> keyword_set().

> In fact it is "is_defined_and_uneven" !

> Just try to pass var=2 into a routine and print keyword_set(var). Hope,

> David will take notice of this in his article.

>

> Another marginal point about setting default values: I recently learned

> from someone's code (cannot remember whose), to use

> if (n_elements(var) ne 1) then var=default

> instead of

> if (n_elements(var) eq 0) then var=default

>

Hallo Martin,

this is not the best way to set variables because

e.g

```
pro test,var1
```

```
  if (n_elements(var1) ne 1) then var1=2
```

```
help,var1
```

```
end
```

test,var1 & test,var1 & help,var1

You see after executing test, var1 has a value.

Better is:

```
pro test,var1
```

```
if n_elements(var1) gt 0 then in_var1=var1 else in_var1=2
```

```
help,in_var1
```

```
end
```

R.Bauer

>
> The advantage being that you can prevent program crashes when someone
> passes a vector or array in what is supposed to be a scalar.
>
> And, finally: Use keyword_set when you want to make sure the value of a
> boolean flag is defined:
> flag = keyword_set(flag)
> Then, later in the code, it's just
> if (flag) then ...
> Or value = x+y*(flag), etc. which would crash otherwise.
>
> Regards,
> Martin.
>
> |||||\\-----// |||||
> Martin Schultz, DEAS, Harvard University, 29 Oxford St., Pierce 109,
> Cambridge, MA 02138 phone (617) 496 8318 fax (617) 495 4551
> e-mail mgs@io.harvard.edu web <http://www-as/people/staff/mgs/>
