Subject: Re: Conflicting Data structures
Posted by Nando Iavarone on Mon, 28 Jun 1999 07:00:00 GMT
View Forum Message <> Reply to Message

<HTML>
Dirk Fabian wrote:
<BLOCKQUOTE TYPE=CITE>Ideally, i would like the user (me) to be able to
choose a new data file, read it

in, and query it, but i keep get the conflicting data structures
error.
Even

if i exit the program and rerun it, it seems like that structure is
still hanging

around. I can't figure out how or where to zero it out!
What am i missing?</BLOCKQUOTE>
A few weeks ago I had a "Conflicting Data structures". I tried to

redefine a non anonymous structure. I had a file with an header

defining its dimension, and I use them to allocate a structure array.

<P>For example:

<P>pro try_struct__define

    n = 5

    struct = {try_struct, $

a: findgen(n)}

end

<P>pro pippo

    a = {try_struct}

    help, /struct, a

<P>   n = 6

    b={try_struct, $

          a: findgen(n)}

    help, /struct, b

end

<P>To resolve the problem I had to use an anonymous struct.

pro pippo

    n = 5

    a = {$

           a: findgen(n)}

    help, /struct, a

    n = 6

    b={$

        a: findgen(n)}

    a={$

        a: findgen(n)}

    help, /struct, a,b

end
<PRE>--
Nando Iavarone
Advanced Computer System - SPACE DIVISION
via Lazzaro Belli, 23
00040 Frascati - RM
Tel: +39-6-944091 (switchboard)
            9440968 (direct)
E-mail:
    f.iavarone@acsys.it
    FrdndVrn@altavista.net</PRE>
 </HTML>