Subject: Re: Pointers

Posted by davidf on Sat, 14 Aug 1999 07:00:00 GMT

View Forum Message <> Reply to Message

J.D. Smith (jdsmith@astrosun.tn.cornell.edu) enlightens us us with yet another interesting idea of how pointers can be used. (But this time he uses a whimsical style, which I haven't seen from J.D. in a while Oh, wait, it's Friday night. He must of just gotten back from the weekly Astronomy bash. :-)

In any case, I like his articles very much because I always learn something from him. But I am confused by this first statement:

- > I would expand this step to include storing a copy of the pointer
- > elsewhere, to eliminate the problem of dissappearing uvalues so common
- > in non-blocking widget applications.

What disappearing uvalues!? I've never heard of this before, and I like to think of myself as a worldly sort of guy. :-(

If the head is not too bad this morning, J.D., can you elaborate a bit on what this is about? Many thanks.

Cheers.

David

P.S. I just tried that transmogrifying trick J.D. recommended. It \*is\* karmic! :-)

--

David Fanning, Ph.D.

Fanning Software Consulting

Phone: 970-221-0438 E-Mail: davidf@dfanning.com

Coyote's Guide to IDL Programming: http://www.dfanning.com/

Toll-Free IDL Book Orders: 1-888-461-0155