
Subject: Re: xmanager /no_block
Posted by [R.Bauer](#) on Mon, 23 Aug 1999 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

David Fanning wrote:

```
> R.Bauer (R.Bauer@fz-juelich.de) writes:
>
>> How did I get the NO_BLOCK state without using xmanager.
>>
>> I have written a small interface where I don't want the controll of the
>> functions by xmanager. Because
>> xmanager blocks a new event as long if it is running the one before.
>> I have written my own event manager for this application so I am able to
>> create events during an event is processed.
>>
>> This all is working really good and fast!
>>
>> The only thing I momentanly don't know is:
>> How did the NO_BLOCK by xmanager work?.
>>
>> What is the command for widget_control to get this mode?
>
> Here is the command in XMANAGER:
>
> if keyword_set(no_block) then WIDGET_CONTROL, $
>   /XMANAGER_ACTIVE_COMMAND, id
>
> I'd be using this only if I *REALLY* knew what I was
> doing. :-)
>
```

This won't work,

may be I don't know where I have to use it.

```
WIDGET_CONTROL, /REALIZE, map.base_0, set_uval=map
WIDGET_CONTROL, /XMANAGER_ACTIVE_COMMAND, map.base_0
```

R.Bauer
