
Subject: Re: xmanager /no_block
Posted by [davidf](#) on Sun, 22 Aug 1999 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

R.Bauer (R.Bauer@fz-juelich.de) writes:

- > How did I get the NO_BLOCK state without using xmanager.
- >
- > I have written a small interface where I don't want the controll of the
- > functions by xmanager. Because
- > xmanager blocks a new event as long if it is running the one before.
- > I have written my own event manager for this application so I am able to
- > create events during an event is processed.
- >
- > This all is working really good and fast!
- >
- > The only thing I momentanly don't know is:
- > How did the NO_BLOCK by xmanager work?.
- >
- > What is the command for widget_control to get this mode?

Here is the command in XMANAGER:

```
if keyword_set(no_block) then WIDGET_CONTROL, $  
    /XMANAGER_ACTIVE_COMMAND, id
```

I'd be using this only if I *REALLY* knew what I was
doing. :-)

Cheers,

David

--

David Fanning, Ph.D.
Fanning Software Consulting
Phone: 970-221-0438 E-Mail: davidf@dfanning.com
Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
Toll-Free IDL Book Orders: 1-888-461-0155
