
Subject: Re: IDL 5.1.1: Going from True_Color to Pseudo_Color on one session
Posted by [davidf](#) on Tue, 07 Sep 1999 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

Bill Capehart (wcapehar@silver.sdsmt.edu) writes:

> Can we bounce between
> device, true_color=24 and
> device, pseudo_color=8
>
> in a single session,
>
> Three of used to this all the time in old versions of IDL and 'Wave and
> either something has changed or we've gone foggy and forgot the magic
> missing step. We've used it before after and inbetween "window" commands
> and nothing has worked.
>
> The only way for it to work is to use one in a given session and stick with
> it.
>
> It's got to be something simple... Ideas?

Uh, switch back to PV-Wave, where you COULD do this
if no windows were currently open. But it ain't gonna
happen in *any* version of IDL. :-)

Cheers,

David

P.S. Let's just say RSI believes in commitment.
And I believe it in too. Especially since I have the
only book out that shows you how to write programs that
work the same in either of these two environments. :-)

--

David Fanning, Ph.D.
Fanning Software Consulting
Phone: 970-221-0438 E-Mail: davidf@dfanning.com
Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
Toll-Free IDL Book Orders: 1-888-461-0155
