Subject: Re: PickData Method on IDLgrWindow Object Posted by Michael Plonski on Thu, 11 May 2000 07:00:00 GMT View Forum Message <> Reply to Message

You don't mention if things worked differntly in IDL 5.3. A detailed description of pickdata from RSI follows.

A while back, I was having a lot of difficulty understanding pickdata and select, since pickdata appeared to ignore the object (model) that you pass it. I didn't save the full thread of discussion with RSI but the key concept that was throwing me (quoted from the RSI response) was:

"It is true that PickData DOES NOT check to see if the x,y is within the specified object. But that is precisely what Select is for."

This might be your problem, as I was getting what appeared to be incorrect values from pickdata as well. If you want to see strange things, overlay a surface above an image plane and then look at pickdata results when the surface is a mesh vs solid. There was no easy way to know with pickdata if you saw through the surface to the image plane or hit a grid line on the mesh surface.

Hope this helps.

Mika Plancki

MING I IOUSKI
Subject:
Re: IDLgrWindow:Pickdata
Date:
Wed, 2 Feb 2000 14:57:55 -0700
From:
RSI E-mail Support <support@rsinc.com></support@rsinc.com>
To:
"'mplonski@aer.com'" <mplonski@aer.com></mplonski@aer.com>

## Mike:

Using Select first and then Pickdata is NOT a kluge. It is that way by design, which means both IDL and the external tools which IDL uses to render graphics (such as OpenGL). The external tools have their own limitations, which I am sure you can understand.

The Select operation (which means the OpenGL Select function call) is particularly expensive, since it performs an "invisible" rendering of an entire scene, creating a list of objects that are in the selection box.

The IDL Object Graphics designers chose, wisely, to separate the Select and

Pickdata operations, so that users would not be forced to pay the penalty of

the Select operation, when it is not really needed. The case where there is

only one object in a model would never require a Select operation; in this

case, you are ready to use Pickdata. It turns out to be fairly common for

complex scenes to have several models, where some of the models contain one

object. For this reason alone, it is important that the Pickdata method NOT

perform a Select operation "under-the-hood."

I have included, below, some comments from one of our Objects Graphics designers. I think you will find them very informative.

Sincerely,

Doug Loucks
Technical Support Engineer
Research Systems Incorporated

Phone: (303)413-3920 FAX: (303)786-9909 Email: support@rsinc.com

Please include my name on the Subject line of email replies. Thanks!

----- Comments from one of our Object Graphics developers:

First, let me explain briefly how Select and PickData work.

Select() performs an "invisible" rendering of the entire scene, performing

hit testing within the selection box for each object in the scene. Objects

that are "drawn" into the selection box are returned in the object list.

PickData() simply reads the Z-buffer at the specified x,y to see if anything

at all got drawn at that location. If something was drawn there, the

following happens: PickData obtains the transform associated with the object you specified in the call to PickData. It does not matter what Select did the last time you called Select. (Select and PickData are completely unrelated) It also does not matter where the x,y is. PickData

just obtains that object's user->screen transform and computes the inverse-transpose of that transform. It then multiplies the specified x,y

by this inverse transform to obtain the corresponding data space coordinates

of the specified x,y. All it does is multiply the specified x,y by an object's inverse transform if SOMETHING was drawn at that x,y. If x,y was

on some other object, the returned user space point will be \*in terms of\* or

\*relative to\* the object specified in the call to PickData. For example suppose you have a sphere centered at (0,0,0) with radius=2 and a sphere located at (5,5,5) with radius=2. If you call PickData with an x,y located

in the middle of the second sphere with the first sphere used as the reference, you will get a returned user data coordinate of (5,5,?), instead

of the expected (0,0,?) because you used the first sphere's transform. Even

though the pick was made beyond the bounds of the first sphere.

We specify a "graphic" object, instead of a model, in PickData, because each

graphic object in a given model can have its own unique transform, which may

be different from the model's transform. Why? Each graphic object has an

additional transform associated with it called the COORD\_CONV transform, specified by the XCOORD\_CONV, YCOORD\_CONV, and ZCOORD\_CONV properties.

these properties are not specified, and left as their default values, then

the graphic object's transform WILL be the same as the transform of the model that contains that graphic object. But, in general, they are not the

same. So, the suggestion of passing a model object in PickData instead of a

graphic object does not work out well. Besides, the problem at hand would

still exist if we used a model as the reference for the inverse transform to

apply because there may be more than one model rendered at a given x,y.

There are several approaches to addressing the problem of associating the

correct model with PickData.

1) Invoke the Select method every time before calling PickData. Use one of

the objects returned by Select as the reference object for PickData. If there are multiple objects returned by Select, you need to deal with that

depending on the application. If there are no objects, there is no hit and

no reason to call PickData. If you do call PickData, the result will be in

terms of the object returned by Select.

If you want to call PickData again, for another x,y, then you really need to

call Select again first, to make sure that you get the right object associated with the new x,y. For example, if you are tracking the mouse cursor and updating a "read-out" with object data values, then you really

need to call Select and PickData for every mouse movement event. This may

seem expensive, and it might be for very complex models. But for most cases, Select is fast enough to remain interactive.

It is true that PickData DOES NOT check to see if the x,y is within the specified object. But that is precisely what Select is for. Therefore, it

is not a kludge to call Select first; it is by design. The only thing that

PickData knows about the supplied object is its transform - PickData has no

idea where the object actually is on the screen.

Perhaps the "Pick" part of the PickData method was poorly named and is partially responsible for the confusion. PickData does not perform a "pick"

as the PHIGS picking functions do. Perhaps you are thinking that PickData

is a full-fledged PHIGS pick - it is not. It just performs a vertex multiply by a certain inverse transform, if the screen was dirty there.

So, why not just have PickData perform a "Select" inside of PickData??? Probably because the designers of this function thought that it was better

to give the user the choice and control over performing these two steps vs.

always doing them both. The obvious example is the case of a single obiect

- you don't need to call Select before PickData.

I think that this approach is the best, but here are some others.

2) Create (I don't mean draw one) a bounding box for each object. Call PickData all you want without calling Select and see which bounding box the

data coordinate returned by PickData is inside of. This only works well where the bounding box encloses the object with little or no extra space and

where objects don't interfere with each other. You would also have to be

careful about using COORD\_CONV and which object you use for the reference

object in PickData.

3) Create a "mask" of the object you want PickData to be sensitive to in

IDLgrBuffer by rendering just the one object into the buffer. If there is a

non-background color in the buffer at the specified x,y, then you have a hit

and can call PickData to get the values.

----- end of comments -----

## Richard Tyc wrote:

- > Has anyone noticed any differences with the Pickdata method in the IDL 5.3.1
- > release.

- > I have a fairly complex window with one main model (oModel) which has
- > several other Models added to it each of which having many objects (such as
- > Polylines, texture-mapped polygons etc.) and each having a different
- > transform.

- > Using the following statement on the overall model (allowing the user to
- > pick anything on screen):
- > pick = sState.oWindow->PickData(sState.oView,\$
- sState.oModel, \$ >
- [sEvent.x,sEvent.y],dataxyz) >

- > The data point, dataxyz, never seems to look right. Even when I select a
- > point on a IDLgrAxis object (which belongs directly to oModel), I never get
- > the expected data point (ie. picking on the x axis should return a point

- > with the range [ 0.0-1.0, 0 , 0 ] but there always seems to be some
- > component of y
- > and z ?? It does however return correctly if I have selected the line (axis)
- > or hit the background.

>

> Anyone know whats going on or have similar experience ?

>

> Rich