
Subject: Re: Arrays of Structures

Posted by [Ben Tupper](#) on Wed, 21 Jun 2000 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Ah!

I think I get it. Anonymous means anonymous... but it is still unique (until redefined).

```
S1 = {a:0, b:.1, c:"}
```

```
A = Replicate(S1,3)
```

```
S2 = S1
```

```
S2.c = 'bob'
```

```
A[1] = S2
```

```
IDL> help, s1,s2,/str
```

```
** Structure <37d658>, 3 tags, length=16, refs=3:
```

```
  A      INT      0
```

```
  B      FLOAT    0.100000
```

```
  C      STRING   "
```

```
** Structure <37d658>, 3 tags, length=16, refs=3:
```

```
  A      INT      0
```

```
  B      FLOAT    0.100000
```

```
  C      STRING   'bob'
```

```
IDL> S1 = {X:1, Y:'y'}
```

```
IDL> help, s1,/str
```

```
** Structure <37fda8>, 2 tags, length=12, refs=1:
```

```
  X      INT      1
```

```
  Y      STRING   'y'
```

Thanks,

Ben

--

Ben Tupper

Bigelow Laboratory for Ocean Science

tupper@seadas.bigelow.org

pemaquidriver@tidewater.net
