Subject: Re: Top 10 IDL Requests Posted by Craig Markwardt on Tue, 18 Jul 2000 07:00:00 GMT View Forum Message <> Reply to Message

```
landsman@my-deja.com writes:
> In article <on66q4a433.fsf@cow.physics.wisc.edu>,
   craigmnet@cow.physics.wisc.edu wrote:
>
>
>> * A way to index strings like arrays.
>>
    I know we can use STRMID and STRPUT, but it seems that an array-like
>>
    notation would fit so much better with the philosophy of IDL.
>>
>>
>
...deletia...
>
```

- > But I am not sure that such a change would be desirable. First of
- > all would be the difficulty in making a syntax change backwards
- > compatible. The change of the string syntax from V1 to V2 probably
- > required more coding changes than any other syntax change ever made to
- > IDL. Also, some syntax would become more complicated -- for example, the
- > current extraction of elements of a string array st1 = st[3:5] would
- > have to become st1 = st[*,3:5]. V5.3 introduced many string
- > processing enhancements (e.g. STRMID now accepts vector parameters), so
- > I think all the functionality of the array notation is now available in
- > then string processing functions. Finally, one can always index strings
- > like arrays by first converting them with BYTE().

I agree that standard array indexing syntax wouldn't mix too well with accessing strings. On the other hand we do already have the X.(SUBSCRIPT) notation for structures, which could perhaps be adapted for strings as well.

```
IDL> value = '0123456789'
IDL> value.(4:5) = '--' ;; pre-beta!
IDL> print, value
0123--6789
```

This is intuitive to me at some level. You use the "." notation to get at the internals of a structure. The same notation could get at the internals of a string.

For that matter, it would be nice, but probably hard to implement, to be able to use range and "*" notation for structures in the same way.

Craig

Craig B. Markwardt, Ph.D. EMAIL: craigmnet@cow.physics.wisc.edu Astrophysics, IDL, Finance, Derivatives | Remove "net" for better response