
Subject: Re: Funny math?

Posted by [Alex Schuster](#) on Thu, 20 Jul 2000 07:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Simon de Vet wrote:

```
> I've got some arrays with data. None extend past 3 decimal places.  
>  
> 'print, filterfunc(0,0,half1), filterfunc(0,0,half2+200)'  
> produces:  
> '537.100    528.300'  
>  
> 'print, filterfunc(0,0,half1) - filterfunc(0,0,half2+200)'  
> produces:  
> '8.79999'  
>  
> What's up with that?
```

It works better if you declare filterfunc as a DBLARR instead of a FLTARR.

```
IDL> print, 537.1  
537.100
```

This looks good, but the value is rounded. Internally, this float is stored not exactly with 3 decimal places, so if you print more, you get this output:

```
IDL> print, 537.1, format='(F12.8)'  
537.09997559
```

With doubles instead of floats:

```
IDL> print, 537.1d  
537.10000
```

More decimal places:

```
IDL> print, 537.1d format='(F12.8)'  
537.10000000
```

Even more decimal places:

```
IDL> print, 537.1d, format='(F20.15)'  
537.10000000000000023
```

```
IDL> print, 537.1d - 528.3d  
8.8000000
```

Alex

--

Alex Schuster Wonko@weird.cologne.de
alex@pet.mpin-koeln.mpg.de

PGP Key available
