

---

Subject: [Q]: ID analog to FORTRAN "sign" function  
Posted by [Rostyslav Pavlichenko](#) on Sat, 07 Oct 2000 05:34:21 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

I need help, I am a new to the IDL.

Does the IDL have something close to Fortran SIGN (DSIGN... so on...) functions

IN FORTRAN:

Elemental Intrinsic Function (Generic):

Returns the absolute value of the first argument times the sign of the second argument.

Syntax:

=====

result = SIGN (a, b)

a (Input) Must be of type integer or real.

b Must have the same type and kind parameters as a.

Results:

=====

The result type is the same as a.

The value of the result is

| a | if b >= zero

and -| a | if b < zero.

--

Best regards, and thank you in advance

=====

Dr Rostyslav Pavlichenko

Research Center for  
Development of Far Infrared Region  
Fukui University

Bunkyo 3-9-1, Fukui 910-8507 Japan

phone: [+81] 776 27 8972

fax: [+81] 776 27 8752

fax: [+81] 776 27 8750

<mailto:slavik@maxwell.apphy.fukui-u.ac.jp>

=====

---

Page 2 of 2 ---- Generated from [comp.lang.idl-pwave archive](#)