Subject: Re: IDLWAVE 4.7/Tutorial

Posted by Henkie on Wed, 13 Dec 2000 08:47:30 GMT

View Forum Message <> Reply to Message

```
"Carsten Dominik" <dominik@astro.uva.nl> wrote in message
news:qzu1yvden8j.fsf@antares.astro.uva.nl...
>>>> "H" == Henkie <deckard 007nospam@deja.com> writes:
>
>
>>> Install IDLWAVE 4.7, where this is the default.
 H> Did so. Still not working. What can this be?
>
 I have no idea. Works for me. What do you get if you type
> C-h k UP
> where UP is the cursor key?
---- Original Message -----
From: "Carsten Dominik" <dominik@astro.uva.nl>
Newsgroups: comp.lang.idl-pvwave
Sent: Tuesday, December 12, 2000 3:19 PM
Subject: Re: IDLWAVE 4.7/Tutorial
>>>> "H" == Henkie <deckard_007nospam@deja.com> writes:
>>>> Install IDLWAVE 4.7, where this is the default.
>
> H> Did so. Still not working. What can this be?
 I have no idea. Works for me. What do you get if you type
> C-h k UP
> where UP is the cursor key?
It says
"up runs 'previous-line'
'previous-line' is an interactive compiled Lisp function
-- loaded from "simple.elc" "
Is this how it should be?
> Remove the (setq idlwave-library-path "/home/henks/progs/idl") - it
> will keep IDLWAVE from doing the right thing.
```

OK, I've found the problem. It is not related to idlwave. I'm running CDE on HP-UX and it appears that if I launch something from the deskop (like XEmacs), it does not run in my own environment. So it has no access to my environment variables. Can you believe this? It took me quite long to find out.

Well, nevermind, sorry and thanks for trying to help.

Henk