Subject: Re: How to redirect stdout & stderr from a Windows app? Posted by R.Bauer on Wed, 24 Jan 2001 12:15:40 GMT

View Forum Message <> Reply to Message

Dave Greenwood wrote:

>

- > I have a windows app (NT 4, IDL 5.3) that apparently screws up occasionally.
- > That is, it doesn't respond to certain buttons, sliders, etc. Of course it
- > hasn't failed any of the times I've tried it in the IDE. Is there any way
- > to redirect stdout and stderr so I can capture IDL messages, PRINT output,
- > etc. in a file? I've tried invoking runtime IDL from a DOS window with ">
- > foo.bar" but I never get any output in foo.bar although my app starts. And,
- > of course, I can't close or reopen units -1 or -2.

>

If you take a look at

"Diverting IDL Output" or "Initialization"

in the online help

Diverting IDL Output:

When using a tty-based interface (UNIX or VMS), IDL sends its output to the screen for the user to see. When using a GUI based interface (any platform), the output goes to the log window. The default output function is automatically installed by IDL at startup. To divert IDL output to a function of your own design, use IDL_ToutPush() and IDL_ToutPop() to change the output function called by IDL. Internally, IDL maintains a stack of output functions, and provides two functions (IDL_ToutPush() and IDL_ToutPop()) to manage them. The most recently pushed output function is called to output each line of text. Output functions of your own design should have the following type definition:

typedef void (* IDL_TOUT_OUTF)(int flags, char *buf, int n);

. . .

Who is able to share IDL_ToutPush() and IDL_ToutPop() functions?

Reimar

--

Reimar Bauer

Institut fuer Stratosphaerische Chemie (ICG-1) Forschungszentrum Juelich email: R.Bauer@fz-juelich.de

a IDL library at ForschungsZentrum J�lich http://www.fz-juelich.de/icg/icg1/idl_icglib/idl_lib_intro.h tml

http://www.fz-juelich.de/zb/text/publikation/juel3786.html