Subject: Re: Running IDL from cron
Posted by Craig Markwardt on Thu, 22 Feb 2001 18:44:23 GMT
View Forum Message <> Reply to Message

Gwyn Fireman < Gwyn. Fireman @gsfc.nasa.gov> writes:

> Hi, everyone -

>

- > With Deja gone and Google barely functional I have to ask here what I'm
- > sure has been addressed before:

Heh, I tried this in my newsgroup archive and nothing found. Hmm.

The main problems I've found with running cron jobs are:

- 1. environment variables not set, and
- 2. programs won't run because path is not set right (consequence of #1)

The answer to number 2 is to specify all program paths explicitly. As for number 1, I would say that you should to write your shell script to set those variables explicitly as well, and bypass your .cshrc. Something like this:

#!/bin/sh HOME=/home/fireman \$HOME/bin/setup\_dirs

Good luck.

IDL\_PATH=+\$HOME/lib/idl:+/usr/local/rsi/idl/lib EXPERIMENT\_DIR=/data/fireman /usr/local/bin/idl \$HOME/scripts/run\_job.pro

This way everything is explicit and there isn't a chance for cron to monkey with it.

Craig	
<b></b>	
,	craigmnet@cow.physics.wisc.edu Remove "net" for better response