
Subject: Re: Am I stupid?

Posted by [colinr](#) on Wed, 11 Jul 2001 09:56:43 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Tue, 10 Jul 2001 08:53:30 -0500,

Liam E. Gumley <Liam.Gumley@ssec-nospam.wisc.edu> wrote:

> Colin Rosenthal wrote:

>>

>> pro stupid,a=a,a1=a1

>>

>> print,'a=',a

>> print,'a1=',a1

>>

>> end

>>

>> IDL> stupid,a=1,a1=2

>> % Ambiguous keyword abbreviation: A.

>>

>> so is there a sensible way around this? What I'm actually trying to

>> do is to have a keyword AXISCOLOR in a routine that also accepts

>> the AX keyword. I know I could call it something different but am I

>> just being a whiny luser if I think the above code should work

>> as is?

> According to the IDL documentation:

>

> "Keywords can be abbreviated to their shortest unique length"

>

> In your case, the keyword AX precludes the use of another keyword which

> begins with the letters "AX". A good rule of thumb is to make the first

> 3 characters of each keyword unique.

Thanks Liam, but I didn't invent the "AX" keyword!

--

Colin Rosenthal

Astrophysics Institute

University of Oslo
