
Subject: Re: PostScript and pixmap

Posted by [Rick Towler](#) on Thu, 26 Jul 2001 15:16:36 GMT

[View Forum Message](#) <> [Reply to Message](#)

Why do you need to place the pixmap into a PS plot? Can you just set the plotting device (using SET_PLOT) to PS and re-plot your data? If you put your plotting commands in a subroutine you could easily save it in all sorts of formats by using SET_PLOT and DEVICE and calling your plotting routine.

If you NEED to do it the hard way, you do something like this:

```
image = TVRD()  
SET_PLOT, 'PS'  
DEVICE, filename='plot.ps'  
TV, image  
DEVICE, /CLOSE
```

There are a lot of details I left out but this should get you started.

If you are new to PS output with IDL I suggest David Fanning's IDL book. You might also want to check out Liam Gumley's new book too. Both are available thru Amazon.

-Rick Towler

<lalassne@Mines.EDU> wrote in message
news:Pine.A41.4.33.0107251802370.98512-100000@slate.Mines.ED U...

> I am trying to take a plot that I have created and make it so that the
> user can save it in several formats. I was hoping to include Post script
> the plot has been put into a pixmap window

>

>

> - Lisa A. Lassner

>

>

> -----

> "We cannot do great things on this earth. We can only do small things
> with great love."

>

> -Mother Teresa

>
