
Subject: Re: CASE a UNAME??

Posted by [Logan Lindquist](#) on Thu, 25 Oct 2001 04:29:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=Content-Type content="text/html; charset=iso-8859-1">
<META content="MSHTML 6.00.2600.0" name=GENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=#ffffff>
<DIV><FONT face=Arial size=2>Wait I guess <FONT face=Arial
size=2>'find_by_uname' really doesn't work if I want to find which Widget_Button
called my event handler function. Back to square one. haha</FONT></FONT></DIV>
<DIV><FONT face=Arial size=2></FONT>&nbsp;</DIV>
<DIV><FONT face=Arial size=2>Logan</DIV>
<DIV>&nbsp;</DIV>
<DIV>&nbsp;</DIV>
<DIV>&nbsp;</DIV>
<DIV></FONT>"Logan Lindquist" &lt;<A
href="mailto:llindquisit@mrdoc.cc">llindquisit@mrdoc.cc</A>&gt; wrote in message
<A
href="news:9r83gg$k2u$1@sulawesi-fi.lerc.nasa.gov">news:9r83gg$k2u$1@sulawesi-fi.lerc.nas
a.gov</A>...</DIV>
<BLOCKQUOTE dir=ltr
style="PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; BORDER-LEFT:
#000000 2px solid; MARGIN-RIGHT: 0px">
<DIV><FONT face=Arial size=2>Umm, nevermind. I found it. </FONT></DIV>
<DIV><FONT face=Arial size=2></FONT>&nbsp;</DIV></BLOCKQUOTE></BODY></HTML >
```
