

Posted by [Logan Lindquist](#) on Thu, 25 Oct 2001 03:44:50 GMT

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=Content-Type content="text/html; charset=iso-8859-1">
<META content="MSHTML 6.00.2600.0" name=GENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=#ffffff>
<DIV><FONT face=Arial size=2>I would like my program to do a CASE statement in
an event handler procedure that is the same for two different options in the
menu of my program. Say I want to change the window size by selecting a
different option in my menu. By doing a CASE statement on the UNAME of the
different options I can figure out which option created the event? So I guess
the Question of the hour is: What is the best way to find which Widget_Button
created an event in a general event handler procedure called by several such
Widget_Button's? </FONT></DIV>
<DIV><FONT face=Arial size=2></FONT>&nbsp;</DIV>
<DIV><FONT face=Arial size=2>I seem to remember seeing this implemented
somewhere, can't remember exactly where so I figured I would ask everyone
tonight before I left work and start looking for how it's done in the morning.
</FONT></DIV>
<DIV><FONT face=Arial size=2></FONT>&nbsp;</DIV>
<DIV><FONT face=Arial size=2>Thank You,&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&~</FONT></DIV>
<DIV><FONT face=Arial size=2>Logan Lindquist</FONT></DIV></BODY></HTML>
```