

---

Subject: Re: WIDGETS

Posted by [sjt](#) on Thu, 01 Sep 1994 12:07:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

mallozzi@ssl.msfc.nasa.gov wrote:

: I recently began to use IDL WIDGETS (on DEC ALPHA) and I have a minor  
: problem: I created a base WIDGET with multiple editable text children  
: to be used as  
: an editable menu. I invoke the WIDGET and register it with XMANAGER, with  
: the keyword JUST\_REG. When I want control of the WIDGET, I type  
: XMANAGER, widget\_id. The problem is as follows: I want to be able to  
: desensitize some of the children, so the user can only alter a single  
: menu entry (I am running a complicated IDL code  
: concurrently). I thought I could destroy the WIDGET and rebuild it with  
: only one child sensitive. Is this possible, or is there a more  
: appropriate method? Thanks -Bob

If you save the ID's of the widgets which you want to change in a common  
block, then you can just use WIDGET\_CONTROL, SENSITIVE=1 (or 0) to  
(de)sensitize the relevant widgets.

--

James Tappin, School of Physics & Space Research

University of Birmingham

[sjt@xun8.sr.bham.ac.uk](mailto:sjt@xun8.sr.bham.ac.uk)

"If all else fails--read the instructions!"

O\_\_  
-- V`