
Subject: Re: Tick formatting

Posted by [Mark Hadfield](#) on Sun, 03 Feb 2002 20:53:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

<gary.hodgesREMOVE@cires.colorado.edu> wrote in message
news:a3esa9\$seri\$1@news.nems.noaa.gov...

> I've almost got what I'm after...

>

> I'm plotting data that runs from zero to 180 degrees. I'd like my
> ticks/labels to go zero -> 90 -> zero. The X axis will actually run
from -5

> to 185, but I would like the ticks and labels to start and end at the zero

> and 180 positions. What I want to end with should look like (ticks
centered

> on numbers of course):

>

> | | | | | | | | | | | | |
> 0 15 30 45 60 75 90 75 60 45 30 15 0

>

> I'm getting an extra zero, i.e., 0 0 15 30, and the values are right
> displaced under the tickmark. This is my best reproduction...

>

> | | | | | | | | | | | | |
> 0 0 15 30 45 60 75 90 75 60 45 30 15 0

>

> I've set the following:

>

> !X.TICKS=13

> !X.TICKV=[0,15,30,45,60,75,90,105,120,135,150,165,180]

> !X.TICKNAME=[0,15,30,45,60,75,90,75,60,45,30,15,0]

As a general rule, you can get more robust and simpler code if you avoid
specifying TICKNAME directly. Try to use TICKFORMAT instead. Define a
function something like this:

```
function myticks, direction, index, value, level
  compile_opt IDL2
  ;; Warning: not tested!
  return, strtrim(round(value < (180-value)))
end
```

and specify !X.TICKFORMAT='myticks'. This doesn't avoid the need to also
specify !X.TICKS and/or !X.TICKV but it avoids the risk that your tick
labels will look right but actually be incorrect.

Mark Hadfield

m.hadfield@niwa.co.nz <http://katipo.niwa.co.nz/~hadfield>

