Subject: Re: correction objects and call external
Posted by Gert on Tue, 12 Feb 2002 20:17:14 GMT
View Forum Message <> Reply to Message

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=Content-Type content="text/html; charset=windows-1252">
<META content="MSHTML 5.50.4912.300" name=GENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=#ffffff>
<DIV><FONT size=2>Off course the last function must contain self.hComm=Temp (in
stead of self.hComm=0l)</FONT></DIV>
<DIV><FONT size=2></FONT> </DIV>
<DIV><FONT size=2> </DIV>
<DIV>
</DIV></FONT>
<BLOCKQUOTE dir=ltr
style="PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; BORDER-LEFT:
#000000 2px solid; MARGIN-RIGHT: 0px">
  <DIV>"Gert" <<A

href="mailto:gert.van.de.wouwer@NO_SPAMpandora.be">gert.van.de.wouwer@NO_SPAMpand
ora.be </A>>
  wrote in message <A

href="news:SJea8.136468$rt4.12914@afrodite.telenet-ops.be">news:SJea8.136468$rt4.12914@
afrodite.telenet-ops.be</A>...</DIV>
  <DIV><FONT size=2>hi,</FONT></DIV>
  <DIV><FONT size=2></FONT> </DIV>
  <DIV><FONT size=2>I try to use a call_external in an object method like
  this:</FONT></DIV>
  <DIV><FONT size=2></FONT> </DIV>
  <DIV><FONT size=2></FONT> </DIV>
  <DIV><FONT face="Times New Roman" size=2>pro MCP2000__DEFINE
 struct =
  {MCP2000, hComm: 0l, status: 0l}
end
</FONT></DIV>
  <DIV><FONT face="Times New Roman" size=2>function MCP2000::Init
self.hComm
  = 0l
return, 1
end
</FONT></DIV>
  <DIV><FONT face="Times New Roman" size=2>function
  MCP2000::InitPort
 self.status=call_external('D:\Cpp\SerCommDll\Debug\SerCommDl
l.dll','InitPortDll',$
 /PORTABLE,'COM1',self.hComm
  ,/UNLOAD)
return, self.status
end
</FONT></DIV>
  <DIV><FONT size=2>the idea is here that self.hComm contains a valid handle,
  but it doesnt - it stays zero.</FONT></DIV>
  <DIV><FONT size=2></FONT> </DIV>
  <DIV><FONT size=2>However, this works</FONT></DIV>
  <DIV><FONT size=2></FONT> </DIV>
  <DIV><FONT face="Times New Roman" size=2>function

MCP2000::InitPort</FONT></DIV>
<DIV><FONT face="Times New Roman"
size=2>Temp=0l
 self.status=call_external('D:\Cpp\SerCommDll\Debug\SerCommDll.dll','InitPortDll',$
/PORTABLE,'COM1',Temp,/UNLOAD)</FONT></DIV>
<DIV><FONT face="Times New Roman" size=2>self.hComm=0l
return,
self.status
end</FONT></DIV>
<DIV><FONT face="Times New Roman"></FONT> </DIV>
<DIV><FONT size=2>any ideas what goes wrong in the first
function????</FONT></DIV>
<DIV><FONT size=2></FONT> </DIV>
<DIV><FONT size=2>Gert</FONT></DIV>
<DIV><FONT size=2></FONT><FONT size=2></FONT> </DIV>
<DIV><FONT size=2></FONT> </DIV>
<DIV><FONT size=2></FONT> </DIV>
<DIV><FONT size=2></FONT> </DIV>
<DIV><FONT size=2></FONT> </DIV></BLOCKQUOTE></BODY></HTML >