Subject: Re: Simple? problem
Posted by Jaco van Gorkom on Tue, 09 Apr 2002 17:52:16 GMT
View Forum Message <> Reply to Message

"Ivan Valtchanov" <ivanv@discovery.saclay.cea.fr> wrote in message news:20020409174917.78c62461.ivanv@discovery.saclay.cea.fr...

- < skipped code of not quite so simple problem ... >
- > This is obviously quite unoptimised two cycles etc. Do you have any ideas, references or do you know if it is already solved in IDL?
- > I have looked for something similar in David Fanning pages and IDL astronomical libraries but I couldn't find something to adapt, maybe I have missed it?

Well, I would start by reading the dimensional juggling tutorial on David's pages

a few times. Then read it again, and practice with the examples.

A nice compromise between the speed penalty for using loops and excessive memory use for array operations is usually found by vectorizing the inner loop

only. Thus FOR j=... until ENDFOR could be replaced by something along the lines of:

ygi = findgen(ny)/ny

dy = rebin(y, 1000, ny, /sample) - rebin(reform(ygi, 1, ny), 1000, ny, /sample)

 $dr = rebin(dx^2, 1000, ny, /sample) + dy^2$

 $arg = dr^2 / rebin(w^2, 1000, ny, /sample) > -20.0$

image[i,0] = total(exp(arg), 1); the total over only the first dimension (1000)

Probably I mixed up all the rebin statements here, since I have not read the juggling tutorial in months. But thirty minutes of toying around on the command

line with help statements usually gets the syntax right.

Jaco

P.S.: It is quite possible that I have misunderstood the meaning or purpose of

your code. Maybe you could describe in words exactly what you want to accomplish?