
Subject: Re: completely reset PostScript device between plots?

Posted by [R.Bauer](#) on Tue, 30 Apr 2002 11:26:43 GMT

[View Forum Message](#) <> [Reply to Message](#)

noymer@socrates.Berkeley.EDU wrote:

```
>
> Reimar Bauer <r.bauer@fz-juelich.de> writes:
>
>> You can save the system variables before each plot and restore them
>> back after one plot.
>>
>> http://www.fz-juelich.de/icg/ [...] /savesysvar.tar.gz + restsysvar.tar.gz
>>
>
> Dear Reimar,
>
> Thanks!
>
> Let me ask you:
>
> This:
>     ; EXAMPLE:
>     ;   save = savesysvar()
>     ;   ..... plotting ....
>     ;   restore, save
>
> Should read:
>     ; EXAMPLE:
>     ;   save = savesysvar()
>     ;   ..... plotting ....
>     ;   restsysvar, save
>
> No? Either that or I'm confused.
>
> Also: it doesn't work. I must be changing something that is not
> saved/restored by your code, which looks to be useful generally speaking.
>
> -Andrew
```

Thanks for this info

Can you try another trick,

```
save,file='sysv.sav',/SYSTEM_VARIABLES
..... plotting ....
restore,file='sysv.sav'
..... plotting ....
```

If this works then I like to add some more ! variables to our routines. (If I know which)

Reimar

--

Reimar Bauer

Institut fuer Stratosphaerische Chemie (ICG-I)
Forschungszentrum Juelich
email: R.Bauer@fz-juelich.de

a IDL library at ForschungsZentrum Juelich
[http://www.fz-juelich.de/icg/icg1/idl_icglib/idl_lib_intro.h tml](http://www.fz-juelich.de/icg/icg1/idl_icglib/idl_lib_intro.html)
=====
