
Subject: resolved strange results: /fill -> /cell_fill
Posted by ddye on Mon, 07 Oct 2002 18:56:43 GMT
[View Forum Message](#) <> [Reply to Message](#)

I've tracked the strange results to my use of /fill, rather than /cell_fill

"Use this keyword (/cell_fill) instead of FILL when you are drawing filled contours over a map, when you have missing data, or when contours that extend off the edges of the contour plot."

Note: Due to the same error I also encountered strange results when attempting to set the data to:

!Values.F_NaN

-d

ddye@fenvironmental.org (Dan Dye) wrote in message news:<dfc65bba.0210041204.50d23a53@posting.google.com>...
> IDL version 5.4 (IRIX mipseb)
>
> I'm encountering strange results using max_value in a contour plot.
> I'm attempting to set unwanted data to a # outside of the range
> (larger than max_value). The funny thing is the contour works fine
> _unless_ the unwanted values are _over_ the max_value. If I set it to
> zero: it plots as zero, 1/2 of the range: the appropriate color, a
> little over the max_value and the whole contour plots white (which is
> appropriate for zero values:.0000001). I read in previous posts that
> this was a legitimate use for max_value, what the heck is going on?
>
> Here is the code in question:
> ;***** snip *****
>
> ;the following can be used to set the bathymetry to any #
> ;// v-- (changed this to lots of values)
> for in=0,58 do begin
> tmparr4[60-in,bathy[in]:*]=9.99E29
> endfor
>
> ;***** row 2 col 3
> contour,tmparr4,distance,depth \$
> ,xrange=[1,60],yrange=[40,0] \$
> ,titl=titl4 \$
> ,levels=scale4zed \$
> ,c_labels=clab \$
> ,C_COLORS=[addC,cvec1] \$
> ,/fill, /closed \$
> ,max_value=ignore \$

> ,FONT=0
