## Subject: Re: IdlGrPolygon - Intersection with planes and lines Posted by Dick Jackson on Wed, 20 Nov 2002 00:36:29 GMT

View Forum Message <> Reply to Message

```
"Martin Downing" <martin.downing@ntlworld.com> wrote in message news:6svC9.1136$Bc.182603@newsfep2-win.server.ntli.net...
```

> Hi all,

>

- > Has anyone written code they wish to share which will give the intersection
- > of a polyon surface\* with a 3D plane, and also the intersection of a polygon
- > surface with a line (3d ray)?
- > One object graphics way to do the plane intersect could be to transform the
- > object to map the plane of intersection onto the z = 0, then use a very
- > small zclip range and the result would be given in image form, however
- > would very much like the "exact" geometric solution, i.e the intersect as a
- > polyline for the plane and point(s) for the line (kind of graphics gems type
- > stuff)

Hi Martin,

For the plane vs. mesh, I think you'll find what you want in the Mesh\_Clip routine and its Cut\_Verts output keyword. IDL 5.6 Help has a nice example program, I hope RSI doesn't mind me posting it here:

## PRO ClippingAMesh

```
; Create a mesh of an octahedron.

vertices = [[0, -1, 0], [1, 0, 0], [0, 1, 0], $

[-1, 0, 0], [0, 0, 1], [0, 0, -1]]

connectivity = [4, 0, 1, 2, 3, 3, 0, 1, 4, 3, 1, 2, 4, $

3, 2, 3, 4, 3, 3, 0, 4, 3, 1, 0, 5, 3, 2, 1, 5, $

3, 3, 2, 5, 3, 0, 3, 5]

; Initialize model for display.

oModel = OBJ_NEW('IDLgrModel')

; Initialize polygon and polyline outline to contain

; the mesh of the octahedron.

oPolygon = OBJ_NEW('IDLgrPolygon', vertices, $

POLYGONS = connectivity, SHADING = 1, $

COLOR = [0, 255, 0])
```

```
oPolyline = OBJ_NEW('IDLgrPolyline', vertices, $
 POLYLINES = connectivity, COLOR = [0, 0, 0])
; Add the polygon and the polyline to the model.
oModel -> Add, oPolygon
oModel -> Add, oPolyline
; Rotate model for better initial perspective.
oModel -> Rotate, [-1, 0, 1], 22.5
; Display model.
XOBJVIEW, oModel, /BLOCK, SCALE = 1, $
 TITLE = 'Original Octahedron Mesh'
; Clip mesh.
clip = MESH_CLIP([1., 1., 1., 0.], vertices, connectivity, $
 clippedVertices, clippedConnectivity, $
 CUT VERTS = cutVerticesIndex)
; Update polygon with the resulting clipped mesh.
oPolygon -> SetProperty, DATA = clippedVertices, $
 POLYGONS = clippedConnectivity
; Display the updated model.
XOBJVIEW, oModel, /BLOCK, SCALE = 1, $
 TITLE = 'Clipped Octahedron Mesh'
Determine the vertices of the clipped plane.
cutVertices = clippedVertices[*, cutVerticesIndex]
; Derive the x and y components of the clipped plane's
: vertices.
x = cutVertices[0, *]
y = cutVertices[1, *]
; Triangulate the connectivity of the clipped plane.
TRIANGULATE, x, y, triangles
; Derive the connectivity of the clipped plane from the
; results of the triangulation.
arraySize = SIZE(triangles, /DIMENSIONS)
array = FLTARR(4, arraySize[1])
array[0, *] = 3
array[1, 0] = triangles
cutConnectivity = REFORM(array, N_ELEMENTS(array))
; Initialize the clipped plane's polygon and polyline.
oCutPolygon = OBJ NEW('IDLgrPolygon', cutVertices, $
```

```
POLYGONS = cutConnectivity, SHADING = 1, $
COLOR = [0, 0, 255])

oCutPolyline = OBJ_NEW('IDLgrPolyline', cutVertices, $
POLYLINES = cutConnectivity, COLOR = [255, 0, 0], $
THICK = 3.)

; Add polyline and polygon to model.

oModel -> Add, oCutPolyline
oModel -> Add, oCutPolygon

; Display updated model.

XOBJVIEW, oModel, /BLOCK, SCALE = 1, $
TITLE = 'Clipped Octahedron Mesh with Clipping Plane'

; Clean-up object references.

OBJ_DESTROY, [oModel]
```

## **END**

I might also mention that IDLDE 5.6 has the excellent multi-line-command-input-pasting feature, so I was able to copy all the lines of this routine, paste them straight into the command input and it worked a charm! (that's one more feature caught up to idlwave-shell... about 300 to go!;-)... I still want a command-line IDL for Windows, any new insight, anyone?)

For the line vs. mesh, I once found some notes once that may apply, but I've wondered if you couldn't do it by defining your line as the intersection of two planes, use Mesh\_Clip twice in succession and get your result from that somehow. These are the notes I found from a helful source at Boston University:

http://cas00.bu.edu/course/cs580/spring2001/mishka/p2/

Hope this is of some help.

```
Cheers,
--
-Dick

Dick Jackson / dick@d-jackson.com
D-Jackson Software Consulting / http://www.d-jackson.com
Calgary, Alberta, Canada / +1-403-242-7398 / Fax: 241-7392
```