## Subject: Re: Plotting to more than one window Posted by notspecified on Fri, 21 Feb 2003 18:41:28 GMT

View Forum Message <> Reply to Message

On Fri, 21 Feb 2003 10:58:36 -0700, David Fanning <david@dfanning.com> wrote:

```
> Do you mean without using an object? Then, no, there
> is no neat and pleasant way to do it. :-)
>
> The messy way, of course, is just to save the appropriate
> system variables:
>
   Window, 1
>
   Plot, data
   p1 = !P
   x1 = !X
   y1 = !Y
   z1 = !Z
   m1 = !Map
>
>
   Window, 2
   Plot, moredata
>
   p2 = !P
   x2 = !X
   y2 = !Y
   z^2 = !Z
   m2 = !Map
>
> Then, when you want to overplot, restore everything:
>
   WSet, 1
   !P = p1
   !X = x1
>
   !Y = v1
   !Z = z1
   !Map = m1
   OPlot, somedataOn1
> Cheers,
```

Neat-- I hadn't realized I could change 'system' variables like that. Opens the door to all sorts of mischief.

Matt Feinstein does not include his email address in the text of usenet postings.

Har∖	ard Law o	of Automotive	e Repair:	Anything	that go	es	away
by it	self will co	me back by	itself.				

Page 2 of 2 ---- Generated from comp.lang.idl-pvwave archive