
Subject: Re: Plotting to more than one window
Posted by [notspecified](#) on Fri, 21 Feb 2003 18:41:28 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Fri, 21 Feb 2003 10:58:36 -0700, David Fanning <david@dfanning.com>
wrote:

```
>
> Do you mean without using an object? Then, no, there
> is no neat and pleasant way to do it. :-)
>
> The messy way, of course, is just to save the appropriate
> system variables:
>
> Window, 1
> Plot, data
> p1 = !P
> x1 = !X
> y1 = !Y
> z1 = !Z
> m1 = !Map
>
> Window, 2
> Plot, moredata
> p2 = !P
> x2 = !X
> y2 = !Y
> z2 = !Z
> m2 = !Map
>
> Then, when you want to overplot, restore everything:
>
> WSet, 1
> !P = p1
> !X = x1
> !Y = y1
> !Z = z1
> !Map = m1
> OPlot, somedataOn1
>
> Cheers,
```

Neat-- I hadn't realized I could change 'system' variables like that.
Opens the door to all sorts of mischief.

Matt Feinstein does not include his email address
in the text of usenet postings.

Harvard Law of Automotive Repair: Anything that goes away
by itself will come back by itself.
