
Subject: Re: passing parameters

Posted by [b.schneider](#) on Sat, 08 Mar 2003 16:52:42 GMT

[View Forum Message](#) <> [Reply to Message](#)

Reimar Bauer <R.Bauer@fz-juelich.de> wrote in message
news:<b483ql\$5t0g\$1@zam602.zam.kfa-juelich.de>...

> Bastienne Schneider wrote:

>

> Dear Bastienne

>

>

> I am using the following trick.

>

>

>

> PRO test

> DEVICE,decomposed=0

> TEK_COLOR

> m=GETENV('VAR')

>

> XYOUTS, 0.5, 0.5, m,color=4,chars=5,/NORM

>

> WAIT,10

> END

>

> This must be saved for runtime usage.

>

>

> And then this is described for linux bash:

>

> a simple shell script named for example test.sh

> with execute rights

>

> export VAR=\$1

> idl -rt='/home/idl/test.sav'

>

>

> test.sh 23 gives the result you wish to have

>

> I believe in M\$ it should work too but I don't remember at the moment

> how environment variables were defined. Was it set ?

>

> regards

>

> Reimar

>

>

Thanks a lot, it works!

I made a DOS batch to run my test.sav and I obtained a wonderfull, big and blue "23" in my window. That's all I wanted :)

Have a nice day

Bastienne
