

---

Subject: Re: IDLgrAxis and scaling  
Posted by [Thomas Gutzler](#) on Thu, 20 Mar 2003 04:13:06 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Mark Hadfield wrote:

> "Thomas Gutzler" <tgutzler@ee.uwa.edu.au> wrote in message  
> news:3E792137.60009@ee.uwa.edu.au...  
>  
>> Mark Hadfield wrote:  
>> Where is the difference between this:  
>>  
>>  
>>> self->GetProperty, TICKTEXT=oticktext, TITLE=otitle  
>>> for i=0,n\_elements(oticktext)-1 do begin  
>>> if obj\_valid(oticktext[i]) then begin  
>>>     oticktext[i]->SetProperty, \$  
>>>         RECOMPUTE\_DIMENSIONS=self.recompute\_dimensions  
>>>     oticktext[i]->GetProperty, FONT=font  
>>>     if not obj\_valid(font) then \$  
>>>         oticktext[i]->SetProperty, FONT=self.font  
>>>     endif  
>>> endfor  
>>  
>> and that:  
>> zaxis->GetProperty, Ticktext=text  
>> text-> SetProperty, Recompute\_Dimensions=1  
>  
>  
> Where does "that" come from? Did I miss a message?

Did my - or your - newsserver mess up my posting ?  
I can't believe that it cuts random lines off. "that" comes from my very  
first posting of "this" thread :)  
<http://groups.google.com/groups?selm=3E783423.4080505%40ee.u>  
wa.edu.au&oe=UTF-8&output=gplain  
ACK?

Tom

---