
Subject: Re: IDLgrAxis and scaling
Posted by [Thomas Gutzler](#) on Thu, 20 Mar 2003 04:13:06 GMT
[View Forum Message](#) <> [Reply to Message](#)

Mark Hadfield wrote:

```
> "Thomas Gutzler" <tgutzler@ee.uwa.edu.au> wrote in message
> news:3E792137.60009@ee.uwa.edu.au...
>
>> Mark Hadfield wrote:
>> Where is the difference between this:
>>
>>
>>> self->GetProperty, TICKTEXT=oticktext, TITLE=otitle
>>> for i=0,n_elements(oticktext)-1 do begin
>>>   if obj_valid(oticktext[i]) then begin
>>>     oticktext[i]->SetProperty, $
>>>       RECOMPUTE_DIMENSIONS=self.recompute_dimensions
>>>     oticktext[i]->GetProperty, FONT=font
>>>     if not obj_valid(font) then $
>>>       oticktext[i]->SetProperty, FONT=self.font
>>>   endif
>>> endfor
>>
>> and that:
>> zaxis->GetProperty, Ticktext=text
>> text->SetProperty, Recompute_Dimensions=1
>
>
> Where does "that" come from? Did I miss a message?
```

Did my - or your - newsserver mess up my posting ?
I can't believe that it cuts random lines off. "that" comes from my very
first posting of "this" thread :)
<http://groups.google.com/groups?selm=3E783423.4080505%40ee.uwa.edu.au&oe=UTF-8&output=gplain>
ACK?

Tom
