
Subject: Re: Slider Question

Posted by [Dave Greenwood](#) on Mon, 07 Jul 2003 21:34:45 GMT

[View Forum Message](#) <> [Reply to Message](#)

In a previous article, Karthikayan Balakrishnan

<lovedale27@hotmail.NOSPAM.com.PLEASEREMOVETHIS> wrote:

> Hello All,

> Is there a way to make a slider in intervals of 5 instead of 1.

> What I mean is this: when I use a slider in a widget, it displays in

> intervals of 1. Is there a way that allows me to start with say 5 and end

> with 100. The second allowable point on the slider is 10, the third 15, the

> fourth 20 and so on. I know that I can multiply by 5 in the event_pro

> procedure but that is not reflected in the slider's label. Any suggestions

> or recommendations? Thanks.

> Karthik.

I created my own variation on RSI's CW_FSLIDER and WIDGET_SLIDER which allowed me to specify intervals (or specific allowable values) for a slider. It's not an object and it's not well tested but you're welcome to it if you're interested. (It requires 4 bit map files to provide Windows-like arrowheads on X displays.)

Dave

Dave Greenwood

Email: Greenwoodde@ORNL.GOV

Oak Ridge National Lab

%STD-W-DISCLAIMER, I only speak for myself
