
Subject: Re: Delete COMMON

Posted by [Pavel Romashkin](#) on Mon, 27 Oct 2003 17:08:42 GMT

[View Forum Message](#) <> [Reply to Message](#)

I am not so sure I regret not being able to run .reset_all or format c:
/y from inside my code. Might throw users off the track :-)

Cheers,
Pavel

David Fanning wrote:

>
> trouble writes:
>
>> I've been running a program with a COMMON block. To delete is, it
>> seems that .reset is the only option. However, I *always* seem to
>> forget to do it so it's only after 1/2 hour of processing, when the
>> results are clearly wrong, that I remember and have to start over.
>>
>> Is there any way to put a .reset in the code, so it always run fresh?
>
> No. Executive commands ("dot commands") can only be
> run from the IDL command line. :-(
>
> Cheers,
>
> David
>
> P.S. Let's just say Common blocks, like taxes, are
> something we have to be responsible for ourselves in
> the eyes of the law.
>
> --
> David W. Fanning, Ph.D.
> Fanning Software Consulting, Inc.
> Phone: 970-221-0438, E-mail: david@dfanning.com
> Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
> Toll-Free IDL Book Orders: 1-888-461-0155
