
Subject: Re: Resolving Built-ins and FORWARD_FUNCTION
Posted by [David Fanning](#) on Thu, 11 Dec 2003 03:49:11 GMT
[View Forum Message](#) <> [Reply to Message](#)

JD Smith writes:

>> Well, as long as you are doing experiments again, does LMGR(/VM) return
>> the same thing as LMGR(/RUNTIME)? I thought I needed to know this the
>> other day for some reason, and I was too lazy to figure it out. :-)
>
> I don't know, but apparently you can use any keyword combo in a Boolean
> OR sense, e.g LMGR(/VM,/RUNTIME) to find out if either is true.

While this is true, it didn't answer my original question, so
I just thought I'd look into it myself. :-)

In a save file running on a RUNTIME license:

LMGR(/Runtime) is set to 1
LMGR(/VM) is set to 0

In the same save file running on the VM:

LMGR(/Runtime) is set to 1
LMGR(/VM) is set to 1

Go figure. :-(

Cheers,

David

--

David W. Fanning, Ph.D.
Fanning Software Consulting, Inc.
Phone: 970-221-0438, E-mail: david@dfanning.com
Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
Toll-Free IDL Book Orders: 1-888-461-0155
