

---

Subject: Re: library and online help  
Posted by [R.Bauer](#) on Wed, 07 Apr 2004 15:02:04 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Steve wrote:

> Hi all,  
>  
> how can I add and IDL library (taken somewhere from the web) to the  
> standard path of my IDL distribution, so that each time I call a  
> procedure/function that is in the library, IDL automatically find it?  
> Do I have to put such library in some directory? where? (I use linux).  
>  
> Just a drop. I have got the new IDL version, but the "old" online help  
> doesn't work anymore :-( Is it right???  
> Only that nasty and NON user-friendly acrobat manual ...  
>  
> Cheers,  
> S.

The simplest way I believe is to use a startup file.

The startup file for our library looks like this one  
[http://www.fz-juelich.de/icg/icg-i/idl\\_icglib/idl\\_source/idl.all](http://www.fz-juelich.de/icg/icg-i/idl_icglib/idl_source/idl.all)

this is an idl script with the syntax restrictions of a journal.

This example is platform independent for the settings for windows, aix and linux. A startup file sets the path in a defined way for several users. It prevents for path order changes by different users which could give different hard to find problems.

A startup file is accessed from idl by setting the env variable IDL\_STARTUP to the file where it is.

for linux a simple one could be

```
!path=!path+':pathToSomewhere:'
```

expand\_path() could be used to expand into sub directories. if they have the '+' sign in front.

```
!path=!path+':+pathToSomewhere:'
```

```
!path=expand_path(!path)
```

regards

Reimar

--

Reimar Bauer

Institut fuer Stratosphaerische Chemie (ICG-I)  
Forschungszentrum Juelich  
email: R.Bauer@fz-juelich.de

-----

a IDL library at ForschungsZentrum Juelich  
[http://www.fz-juelich.de/icg/icg-i/idl\\_icglib/idl\\_lib\\_intro.html](http://www.fz-juelich.de/icg/icg-i/idl_icglib/idl_lib_intro.html)

=====