Subject: Re: Colors in PLOT with IDL Posted by David Fanning on Tue, 25 May 2004 11:11:37 GMT View Forum Message <> Reply to Message

Andreas Ernst writes:

- > what is the argument for PLOT and OPLOT to plot
- > a colored graph in IDL? The argument linestyle is
- > not sufficient, my plot looks still very ugly with
- > different line styles.

Color is a pretty complicated subject. You have to worry about whether your device is 8-bit or 24-bit, whether color decomposition is turned on or off, how many colors can physically be loaded in the color table, etc., etc. It can drive you crazy if you let it.

That's why I use a color program, FSC_COLOR, that makes a lot of these decisions for me and lets me create a plot in a device independent way. The following short program will look identical on your display screen, sent to a PostScript file, run in the Z-graphics buffer, etc.

You can find FSC_COLOR here:

http://www.dfanning.com/programs/fsc_color.pro

And, of course, you can find a LOT of information about color, generally, on my web page. :-)

PRO DrawingColorTest

```
; Create drawing colors.

axisColor = FSC_Color('navy', !D.Table_Size-2)

background = FSC_Color('ivory', !D.Table_Size-3)

dataColor = FSC_Color('indian red', !D.Table_Size-4)

fillColor = FSC_Color('dodger blue', !D.Table_Size-5)

outlineColor = FSC_Color('dark green', !D.Table_Size-6)

; Create data for a plot. Fill the region from x=20 to x=45.

x = Findgen(101)

y = 4 * Sin(x * !DtoR) / Exp( (x-15) / 25.)

lowVal = 20

highVal = 45

; Draw the plot.
```

```
lowY = 4 * Sin(lowVal * !DtoR) / Exp((lowVal-15) / 25.)
 highY = 4 * Sin(highVal * !DtoR) / Exp((highVal-15) / 25.)
 indices = Value_Locate(x, [lowVal, highVal])
 low = indices[0]
 high = indices[1]
 IF x(low) LT lowVal THEN low = low + 1
 IF x(high) GT highVal THEN high = high - 1
 xpoly = [lowVal, lowVal, x[low:high], highVal, highVal]
 ypoly = [!Y.CRange[0], lowY, y[low:high], highY, !Y.CRange[0]]
 PolyFill, [0,0,1,1,0], [0,1,1,0,0], Color=background, /Normal
 PolyFill, xpoly, ypoly, Color=fillColor
 PlotS, xpoly, ypoly, Color=outlineColor, Thick=2
 Plot, x, y, Color=axisColor, /NoData, /NoErase
 OPlot, x, y, Color=dataColor, Thick=3
 END
To run this program at the IDL command line:
 IDL> Window
 IDL> DrawingColorTest
To run this program in the PostScript device:
 IDL> thisDevice = !D.Name
 IDL> Set Plot, 'PS'
 IDL> Device, Color=1, Bits=8
 IDL> DrawingColorTest
 IDL> Device. /Close
 IDL> Set Plot, this Device
Cheers.
David
David Fanning, Ph.D.
Fanning Software Consulting, Inc.
```

Coyote's Guide to IDL Programming: http://www.dfanning.com/